

SAIP2014



Contribution ID : 108

The development of a general purpose Processing Unit for the upgraded electronics of the ATLAS detector Tile Calorimeter

Tuesday 08 Jul 2014 at 14:00 (00h20')

Abstract :

Modern Big Science projects such as the Large Hadron Collider at CERN generate enormous amounts of raw data which presents a serious computing challenge. After planned upgrades in 2022, the data output from the ATLAS Tile Calorimeter will increase by 200 times to over 40 Tb/s! ARM processors are common in mobile devices due to their low cost, low energy consumption and high performance. It is proposed that a cost-effective, high data throughput Processing Unit (PU) can be developed by using several consumer ARM processors in a cluster configuration to allow aggregated processing performance and data throughput while maintaining minimal software design difficulty for the end-user. This PU could be used for a variety of high-level functions on the high-throughput raw data such as spectral analysis and histograms to detect possible issues in the detector at a low level. High-throughput I/O interfaces are not typical in consumer ARM System on Chips but high data throughput capabilities of greater than 20 Gb/s per PU is feasible via the novel use of PCI-Express as the I/O interface to the ARM processors. An overview of the PU is given and the results for performance and throughput testing of Freescale Semiconductor i.MX6 quad-core ARM Cortex-A9 processors are presented.

Award :

Yes

Level :

MSc

Supervisor :

Bruce Mellado, Wits, bruce.mellado@wits.ac.za

Paper :

Yes

Primary authors : Mr. COX, Mitchell (University of the Witwatersrand)

Co-authors :

Presenter : Mr. COX, Mitchell (University of the Witwatersrand)

Session classification : NPRP

Track classification : Track B - Nuclear, Particle and Radiation Physics

Type : Oral Presentation