

# SAIP 2011



Contribution ID : 225

## **Non-linear Fowler-Nordheim plots in thin film polymer-fullerene composite devices: Transition from electron-only to hole-only conduction**

Thursday 14 Jul 2011 at 11:15 (00h15')

### **Content :**

We studied charge injection and transport mechanisms in blends of poly(3-hexylthiophene) (P3HT) and [6,6]-phenyl C61-butyric acid methylester (PCBM), by analysing dark, temperature dependent current-voltage characteristics of the P3HT:PCBM blend thin films sandwiched between aluminium electrodes in a MIM configuration. We present a general method of interpreting Fowler - Nordheim plots of metal/semiconductor/metal devices with pronounced non-linear characteristics by dividing them into several regions based on physical origins. We show that by applying appropriate electric fields it is possible to switch from electron-only conduction to hole-only conduction in a single Al/P3HT:PCBM/Al device. We affirm that electrons can be selectively transported through the lowest unoccupied molecular orbital of PCBM at low applied voltages and low temperatures; and alternatively holes can be transported through the highest occupied molecular orbital of P3HT at higher applied voltages and high temperature, within a single device.

### **Level (Hons, MSc, PhD, other)? :**

PhD

### **Consider for a student award (Yes / No)? :**

No

### **Short Paper :**

Yes

**Primary authors :** Dr. CHIGUVARE, Zivayi (University of the Witwatersrand)

### **Co-authors :**

**Presenter :** Dr. CHIGUVARE, Zivayi (University of the Witwatersrand)

**Session classification :** CMPMS2

**Track classification :** Track A - Condensed Matter Physics and Material Science

**Type :** Oral Presentation