

AOIM2013

Monday 02 September 2013 - Friday 06 September 2013

STIAS Conference Centre

Book of Abstracts

Contents

Mr	1
Imaging the expression of Channelrhodopsin-2 as a directly light-gated cation-selective membrane channel in HEK 293 cells	1
-Strehl ratio, divergence, M2 factor –What is good for describing the propagation of a diffracted laser beam?	1
Dynamic plenoptic perception with adaptive mirror	2
Imaging of solid aerosols produced by optical catapulting	2
The use of Zernike and Q-Polynomials combined for the Representation of Intraocular-Lens Topologies	3
Aberration correction with adaptive optics for lowering the threshold energy for femtosecond laser induced optical breakdown in a water based eye model	4
Adaptive Optics in Astronomy: deblurring the atmosphere	4
Modal decomposition for wavefront reconstruction	5
Layer-oriented adaptive optics for extended objects	5
Adaptive optics for multi-photon microscopy using direct and sensorless measurement	6
Overview and perspectives of Active and Adaptive Optics for Space Optical Applications	6
Constrained optimisation for fast wavefront sensorless adaptive optics in microscopy	7
Propagating aberrated laser beams	8
Active spatial polarization control for microscope objectives	8
Biomedical applications of optics	9
Impact of wavefront aberrations in ultrafast nonlinear optics	9
Free-motion measurement of the beam propagation factor by means of a spatial light modulator.	10
Multi-conjugated adaptive optics for intense femtosecond lasers	11
Computational Testbench and Flow Chart for Wavefront Sensors	11

High resolution in-vivo imaging of the mouse retina using an adaptive optics system with MEMS segmented piston/tip/tilt deformable mirror.	12
Recent advances in high-power fundamental mode thin-disk lasers using intra-cavity deformable mirrors	13
Characterization and application of a deformable mirror for pulse shaping in the Mid-Infrared	13
Modal deformable mirror optimization in sensorless Optical Coherence Tomography . .	14
Ultrafast time compensated monochromator with deformable diffraction gratings	15
High resolution wavefront control using a photocontrolled deformable mirror in closed loop	16
All-digital holographic tool for real-time mode excitation and ~analysis in optical waveguides	16
Utilizing speckle decorrelation for tomographic wavefront sensing (with one wavefront sensor)	17
Manufacturing and Testing of Unimorph Deformable Mirrors for Space Telescopes . . .	17
Optical Design and Optimization of Adaptive Automobile Headlight with Liquid Optical Element and Freeform	18
Compensation of the two-stage phase-shifting algorithms with respect to detuning and harmonics	19
Correction for distortions in holographic nanointerferometers	19
Adaptive Lenses for Displays & Vision	20
Results on the high power testing of screen-printed deformable mirrors	20
Advances in adaptive optics nonlinear microscopy for applications in medical and life sciences	21
Adaptive Optics for Horizontal Propagation Applications	21
Dynamic generation of scattering for high resolution adaptive optics in the eye	22
Phase generation in white light with a 6- Π Liquid Crystal on Silicon (LCoS) device . . .	23
A parametric study of the contributing factors influencing femtosecond pulse shape transfer via difference frequency mixing.	23
Design optimization of an actuator pattern for a unimorph deformable mirror	24
Large Scale Deformable Mirror Based on Bimorph and Stack Actuators	25
Wide field wavefront sensing on extended scenes and possible applications	25
Localization and image reconstruction of inclusions embedded in biological tissue (turbid media) by means of adaptive optical system	26

Real-time high speed adaptive optical system for imaging and laser beam control	26
Artificial model of human eye aberrations proceeded in real-time	27
Recent Advances in MEMS Deformable Mirror Technology	28
Superpenetration Multiphoton Microscopy Enabled Through MEMS DM Technology . .	28
A novel technique to generate and temporally shape multiple pulsed laser beams using 2D-SLMs	29
ADAPTIVE OPTICS FROM MICROSCOPY TO NANOSCOPY	29
Free space prof without Free Space	30
Free Space prop without the free space	30
re	30
Shaping ultrafast pulsed beams in space and time with programmable spatial light modu- lators	30
Achieving the highest intensity from the Orion Laser Facility	31
Quantum Communications along Optical Links with Strong Turbulence	31
Functional Imaging of Single Cells in the Living Eye	32
Welcome Remarks	33
Basics of AOs and adaptive control	33
Basics of deformable mirrors	33
Basics of wavefront sensing	33
Basics of liquid crystals and their use in AOs:	33
AOs in Vision	33
Biomedical imaging with AOs	33
AOs and microscopy	34
Turn key AO systems	34
AOs in ultrafast and ultrahigh power lasers	34
AOs in high precision materials	34
Wavefront correction in large-scale glass laser LFEX	34
Real-time dynamic control of laser modes	35
Quantum communication with OAM entangled photons	35
Producing Kaleidoscope Modes using the Digital Laser	36

1

Mr**Author:** Andrew Forbes¹¹ CSIR**Corresponding Author:** aforbes1@csir.co.za**Abstract content**
(Max 300 words)
Special Chars:

Hello world

2

Imaging the expression of Channelrhodopsin-2 as a directly light-gated cation-selective membrane channel in HEK 293 cells**Author:** Ahmed El-Hussein M.Kamel¹¹ The National Institute of Laser Enhanced Science, Cairo University**Corresponding Author:** a.el-husseiny@niles.edu.eg**Abstract content**
(Max 300 words)
Special Chars:

Channelrhodopsins (ChRs) originated from algae of *Chlamydomonas* genus have been considered as directly light-gated ion channels. In microalgae, their primary function is to direct the organism towards or away from the light stimulus as well to optimize the light conditions needed for photosynthesis. ChR2 originated from *Chlamydomonas reinhardtii* was shown to be involved in generation of photocurrents in this green alga has been found to be 10 times better than ChR1 for the expression in most host cells like *Xenopus* oocytes. Despite of this fact and ChR2 can be easily targeted genetically; many of selective promoters cannot achieve sufficient expression levels of ChR2 for photostimulation. In the present work, HEK 293 cells has been expressed by ChR2 tagged with the fluorescent protein mCherry (ChR2mCherry) in one series of experiments and by ChR2 and mCherry individually in another set of experiments. The results have shown that ChR2 is a directly light-switched cation-selective ion channel upon stimulating the cells with 475 nm blue light. This channel opens rapidly after absorption of a photon to generate a large permeability for monovalent and divalent cations. Furthermore the degree of expression of ChR2mCherry in HEK 293 cells was better than that of ChR2 alone despite the initial thought of being mCherry genes could compete with the ChR2 genes.

Session IX: Space / 3**-Strehl ratio, divergence, M2 factor –What is good for describing the propagation of a diffracted laser beam?****Author:** Kamel AIT-AMEUR¹**Co-authors:** Abdelhalim BENCHEIKH ²; Andrew FORBES ³; Boualem BOUBAHA ⁴; Darryl NAIDOO ³; Michael FROMAGER ¹; Thomas GODIN ¹¹ CIMAP-ENSICAEN,Caen, France

² LOA, Sétif, Algeria

³ NLC-CSIR, Pretoria

⁴ Faculté de Physique-USTHB, Algiers

Corresponding Author: kamel.aitameur@ensicaen.fr

Abstract content
(Max 300 words)
Special Chars:

We consider the transverse characteristics of a laser beam suffering amplitude or phase diffraction. In particular, we consider the correlation or the absence of correlation between the parameters divergence angle, Strehl ratio and M2 factor usually used for describing the focusability of a laser beam. We will also introduce the concept of transverse correlation of a laser beam. We will give concrete examples for which the information holds by the above parameters is contradictory, and can disturb for instance the monitoring of a distributed lensing effect or the determination of the focal volume.

Session VI: Vision / 4

Dynamic plenoptic perception with adaptive mirror

Authors: Davies W. de Lima Monteiro¹; Felipe T. Amaral²; Thiago D. O. Moura²

¹ Associate Professor - OptMA_lab - DEE/UFMG Electrical Engineering Department, Av. Antonio Carlos, 6627 - Pampulha, 31270-010 - Belo Horizonte - MG

² Graduate Program in Electrical Engineering - Federal University of Minas Gerais - Av. Antônio Carlos 6627, 31270-901, Belo Horizonte, MG, Brazil

Corresponding Author: thiagodaniel_moura@hotmail.com

Abstract content
(Max 300 words)
Special Chars:

Plenoptic cameras enable one to take a single shot of a scene and have the focal plane decided upon later, by rendering the custom registered image in a post-processing step[1][2]. This approach takes a fuller advantage of the optics, as the name implies, capturing multiple light fields of a single scene. A given plane can be selected for optimal focus, and naturally all planes within its depth of field; but, by tweaking the rendering algorithm, also multiple distant planes can be presented simultaneously in focus. It works for static images and demands some post computation either on-board or in a PC. We, therefore, wondered whether videos, i.e. a sequence of static frames, could also exhibit such a feature. We aim to present the plenoptic concept applied to dynamic imaging by means of an adaptive mirror coupled to an ordinary camera system. The outcome of our first tests seems to be quite promising when the mirror is driven at an appropriate duty cycle and amplitude, adjusted to the transfer function of the human retina.

There is a myriad of applications that can deploy this concept, ranging from displays to microscopy. In this paper we intend to exploit the experimental setup, the obtained results and the constraints that must be observed for a successful dynamic plenoptic effect.

[1] NG, R. 2005. Fourier slice photography, ACM Trans. Graph., 735-744.

[2] GEORGIEV, T., LUMSDAINE, A. 2010. Focused Plenoptic Camera and Rendering, Journal of Electronic Imaging, Volume 19, Issue 2.

Imaging of solid aerosols produced by optical catapulting

Author: Mahmoud Mohamed¹

Co-authors: Angel Fernandez-Bravo ²; Francisco Javier Fortes ²; Javier Laserna ²; Mohamed Abdel Harith ¹

¹ *The National Institute of Laser Enhanced Science*

² *Department of Analytical Chemistry, Faculty of Sciences, University of Malaga, Spain*

Corresponding Author: mahmoudstar@gmail.com

Abstract content
(Max 300 words)
Special Chars:

The analysis of solid aerosols has a great importance in many fields of applications including atmospheric sciences, process monitoring and control. Optical catapulting OC is a good sampling method and has been used in combination with Laser induced breakdown spectroscopy LIBS for analysis of solid aerosols. In the present study Imaging experiments were performed in order to probe the behavior and dynamics of OC- produced solid aerosols. Two synchronized Nd: YAG lasers have been used, one for optical catapulting at wavelength = 1064 nm and the other for imaging purpose at wavelength = 532 nm. Standard aluminium silicate particles of size ranging from 0.2 to 8 μm have been used as catapulting target. Several parameters relevant to aerosols dynamics have been studied, such as the effect of inter-pulse delay time Δt , the effect of laser fluence as well as the effect of working distance. Experimental velocity values of the solid aerosols have been also obtained.

Session VI: Vision / 6

The use of Zernike and Q-Polynomials combined for the Representation of Intraocular-Lens Topologies

Authors: Luiz Carvalho¹; Monteiro Davies W. de Lima¹; Rodolfo Costa¹

¹ *Graduate Program in Electrical Engineering - Federal University of Minas Gerais*

Corresponding Author: rodolfocosta@cpdee.ufmg.br

Abstract content
(Max 300 words)
Special Chars:

Intraocular lenses (IOLs) have gained a momentum in their development in the last few years as new technologies and materials became available. They are alternative to the natural crystalline lens of the eye in several clinical conditions, especially cataract, which is the most important cause of blindness in the world. IOLs can be divided into three main groups: monofocals, torics and multifocals. This paper focuses on the refractive monofocal IOLs that differ from each other according to the shape of the surface (i.e. spherical or aspheric) and dioptric power. Spherical lenses present peripheral distortion reducing contrast sensitivity. This is minimized with aspheric lenses, based on a conic, usually hyperbolic, topology.

There are numerous possibilities to mathematically represent IOL surfaces. In Ophthalmology, Zernike polynomials have been historically employed as the orthogonal basis for the precise description of recurrent eye-lens topologies as defocus, astigmatism, spherical aberration and coma. However, Zernike polynomials present limitations when describing aspheric surfaces, often requiring a large number of terms for their representation. Recently, Forbes proposed a group of orthogonal polynomials, also known as Q polynomials, that ease the representation and manufacturability of aspheric surfaces [1]. This paper compares the reconstruction of aspheric monofocal IOL surfaces sequentially using the first couple of Zernike and Forbes polynomial terms. We, therefore, propose the investigation of the reconstruction of both rotationally symmetric and asymmetric IOL surfaces in two steps that can be performed in the reverse order as well: 1) reconstruction with the first Zernike terms and 2) reconstruction of the residual surface with Forbes polynomials. This analysis verifies whether the combination of both polynomials renders the reconstruction of relevant ophthalmic surfaces with a prescribed precision and using fewer

terms than required by each basis individually. We believe that successful results will also have a direct impact on adaptive optical systems.

References

- [1] G. W. Forbes, "Characterizing the shape of freeform optics," OPTICS EXPRESS, vol. 20, pp. 2483-2499, 30 January 2012

Session VI: Vision / 7

Aberration correction with adaptive optics for lowering the threshold energy for femtosecond laser induced optical breakdown in a water based eye model

Author: Anja Hansen¹

Co-authors: Alexander Krüger¹; Axel Günther¹; Romain Gêneaux¹; Tammo Ripken¹

¹ *Laser Zentrum Hannover e.V.*

Corresponding Author: a.hansen@lzh.de

Abstract content (Max 300 words) http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=1&target=_blank **Special Chars**:

In vision science, individual eye aberrations often compromise the quality of images of or stimuli to the retina. Here, adaptive optics is an established method for aberration correction. In femtosecond laser ophthalmic microsurgery, optical aberrations of the eye distort the irradiance profile at the laser focus which reduces the precision. Furthermore, the distorted focus increases the required laser pulse energy for the surgery process of laser-induced optical breakdown which increases the risk of collateral damage. For this reason, vitreo-retinal surgery in the posterior part of the eye has so far been considered impossible. The combination of adaptive optics for vision science with a femtosecond laser for ophthalmic surgery could overcome the obstacle of eye aberrations and therefore enable vitreo-retinal laser microsurgery. In this study we used water for modeling eye tissue during optical breakdown. Optical breakdown threshold was determined in single pulse plasma transmission loss measurements. We show that the threshold energy can be considerably reduced when using adaptive optics for aberration correction. For initial aberrations with a root-mean-square wave front error of only one third of the wavelength an adaptive optics aberration correction to the diffraction limit enables a reduction in threshold energy by a factor of three. At twice the threshold the transmitted pulse energy is reduced by seventeen percent. The reduction in both applied and transmitted pulse energy when correcting for aberrations could be transferred from the model eye to ophthalmic applications. With the present work we are confident that ophthalmic surgery could benefit from an aberration correction with adaptive optics, especially with regard to retinal safety. A lowered threshold energy for laser induced optical breakdown poses an important step towards femtosecond laser vitreo-retinal surgery.

Session IX: Space / 8

Adaptive Optics in Astronomy: deblurring the atmosphere

Author: David Buckley¹

Co-authors: Laure Catala²; Steven Crawford²; Timothy Pickering²

¹ *Southern African Large Telescope*

² *SAAO*

Corresponding Author: dibnob@sao.ac.za

Abstract content
(Max 300 words)
Special Chars:

The application of Adaptive Optics in astronomy has been revolutionary for ground based telescopes, particularly those working in the near infrared region of the electromagnetic spectrum. Techniques are rapidly evolving and current systems can already rival space-based telescopes (e.g. the Hubble Space Telescope) in some areas. This talk will briefly review how astronomical AO works and the results that can be achieved. The effects of the atmosphere in causing image degradation will be presented, as will the manner in which we can monitor its effect in real time. Finally the potential future use of Ground Layer AO for the Southern African Large Telescope will be discussed.

Session III: Wavefront Sensing Techniques / 9

Modal decomposition for wavefront reconstruction

Author: Christian Schulze¹

Co-authors: Andrew Forbes²; Daniel Flamm¹; Darryl Naidoo²; Michael Duparré¹

¹ *Institute of Applied Optics, Abbe Center of Photonics, Friedrich Schiller University Jena, Germany*

² *Council for Scientific and Industrial Research, National Laser Centre*

Corresponding Author: christian.schulze@uni-jena.de

Abstract content
(Max 300 words)
Special Chars:

We present a novel method for measuring the wavefront of laser beams based on modal decomposition using correlation filters. Accordingly, the beam under test is correlated with the modes encoded into the filter, which enables the reconstruction of the optical field in amplitude and phase and consequently the determination of Poynting vector and wavefront. The method is applied to aberrated free space Gaussian beams and beams emanating from optical fibers, for both, scalar and vector beams. Results are compared to those of a Shack-Hartmann wavefront sensor revealing excellent agreement, hence proving the high fidelity of wavefront reconstruction.

Session II : Imaging and Microscopy / 10

Layer-oriented adaptive optics for extended objects

Author: Aglae Kellerer¹

Co-author: Richard Myers¹

¹ *Durham University*

Corresponding Author: a.n.c.kellerer@durham.ac.uk

Abstract content
(Max 300 words)
Special Chars:

A key feature of future adaptive-optical systems will be multi-conjugate (MCAO) correction. There are fundamentally two different approaches to MCAO – star-oriented and layer-oriented.

Up to now, MCAO for extended objects uses exclusively a star-oriented approach, which is a natural extension of a conventional AO system. The field-size of a star-oriented MCAO system is however limited due to the difficulty involved in the tomographic reconstruction.

We argue that extended objects – e.g. the retina and biological tissues – are ideal targets for layer-oriented MCAO systems because the wavefront distortions can be sensed continuously over the entire field-of-view. Interestingly, in a layer-oriented approach, the correction is improved with increasing field-sizes. A practical implementation, however, meets current technological limits in terms of detector sizes and read-out frequencies.

Session VII : Imaging and Microscopy / 11

Adaptive optics for multi-photon microscopy using direct and sensorless measurement

Author: Tim van Werkhoven¹

Co-authors: Christoph Keller¹; Hans Gerritsen²; Hoa Truong²; Jacopo Antonello³; Michel Verhaegen³

¹ *Leiden Observatory, Leiden University*

² *Molecular Biophysics, Utrecht University*

³ *Delft University of Technology, Delft Center for Systems and Control*

Corresponding Author: werkhoven@strw.leidenuniv.nl

Abstract content
(Max 300 words)
Special Chars:

Adaptive optics is widely used in astronomy to obtain diffraction-limited images through the turbulent atmosphere of the Earth. Over the last years, adaptive optics has gained the attention of a wider audience including microscopy. In this field, deep imaging in turbid media such as tissue is challenging due to scattering and optical aberrations. Adaptive optics can compensate the tissue aberrations.

We use a coherence-gated wavefront sensing (CGWFS) scheme for multi-photon scanning microscopes using the pulsed, near-infrared light reflected back from the sample. Coherence gating isolates the light from a layer of interest and rejects ghost reflections in the optical system, solving an intrinsic problem for direct wavefront sensing methods.

By interfering the back-reflected light with a tilted reference beam, we create a fringe pattern with a known spatial carrier frequency in an image of the back-aperture plane of the microscope objective. The sample-induced wavefront aberrations distort this fringe pattern and thereby imprint themselves at the carrier frequency, which allows us to separate the aberrations in the Fourier domain from low-frequency noise. A Fourier analysis of the modulated fringe pattern retrieves the wavefront aberrations, and the pulsed laser rejects spurious signals through coherence gating. This wavefront sensing method can directly measure the wavefront which is subsequently corrected using a deformable mirror.

Our method has a reproducibility of $\lambda/86$ peak-to-valley for defocus. We verified our method with a deformable mirror (DM) to measure the wavefront sensing accuracy. We present wavefront measurements of biological samples, and compare our method to sensorless methods, where the feedback loop uses an image quality metric instead. Finally, we will present first results of AO corrected measurements.

Session IX: Space / 12

Overview and perspectives of Active and Adaptive Optics for Space Optical Applications

Author: Pascal Hallibert¹

¹ *ESA-ESTEC*

Corresponding Author: pascal.hallibert@esa.int

Abstract content
(Max 300 words)
Special Chars:

The increasing need for higher resolution for space optical applications has prompted the study of technologies aimed at improving imaging performance beyond what is currently achievable by classical optical systems.

Active Optics and Adaptive Optics are very promising examples of such technologies, potentially allowing to counter in-flight effects (such as thermo-elastic deformations, radiation effects on optical materials, micro-vibrations...) which impact the optical quality of space instruments. They can also potentially decrease the manufacturing complexity of optical component and reduce the outage rate of missions (due e.g. to Sun baffle intrusions or eclipses altering the thermal conditions within the instrument).

This paper gives an overview of the current state-of-the-art of Active/Adaptive Optics developments for Space Applications. It details as well the constraints that such systems would encounter during a Space mission and lists effects affecting image quality that Active/Adaptive Optics could help reduce.

Session VII : Imaging and Microscopy / 13

Constrained optimisation for fast wavefront sensorless adaptive optics in microscopy

Author: Jacopo Antonello¹

Co-authors: Christoph Keller ²; Hans Gerritsen ³; Michel Verhaegen ¹; Tim van Werkhoven ³

¹ *DCSC, Delft University of Technology*

² *Leiden Observatory, Leiden University*

³ *Molecular Biophysics, Utrecht University*

Corresponding Author: j.antonello@tudelft.nl

Abstract content
(Max 300 words)
Special Chars:

Specimen-induced aberrations severely affect the image quality in fluorescence scanning microscopy. Therefore, adaptive optics is used to restore diffraction-limited imaging [1]. Since direct wavefront sensing has been shown to be challenging in fluorescence microscopy, wavefront sensorless adaptive optics techniques have been developed. Instead of attempting to measure the wavefront, a suitable image quality metric is used as a feedback signal for the aberration correction procedure. This is a sequential process that consists of probing different settings of a wavefront correction element (e.g. a deformable mirror) until the corresponding value of the image quality metric is optimised.

Sensorless adaptive optics has been theoretically studied and experimentally demonstrated for different microscopy approaches [2]. In particular it was shown that a model of the image quality metric allows to reduce the time necessary for the aberration correction procedure. This minimises both the overall image acquisition time and undesirable side effects such as photobleaching and phototoxicity.

Here we consider the case when a quadratic polynomial is used to model the image quality metric [3]. This class of models has been widely employed in different microscopy approaches. We show that a robust aberration correction is achieved by solving a suitable constrained optimisation problem. We also show that, exploiting an a priori assumption about the unknown wavefront aberration, an incremental

correction can be applied before the minimum number of measurements necessary to uniquely determine the aberration is reached. Our proposed algorithms are compared with other solutions present in the literature and validated in a laboratory environment.

¹M. J. Booth, "Adaptive optics in microscopy." Philosophical transactions. Series A, Mathematical, physical, and engineering sciences 365, 2829-2843 (2007).

²A. Facomprez, E. Beaupaire, and D. Débarre, "Accuracy of correction in modal sensorless adaptive optics," Opt. Express 20, 2598-2612 (2012).

³J. Antonello, M. Verhaegen, R. Fraanje, T. van Werkhoven, H. C. Gerritsen, and C. U. Keller, "Semidefinite programming for model-based sensorless adaptive optics," J. Opt. Soc. Am. A 29, 2428-2438 (2012).

14

Propagating aberrated laser beams

Author: Cosmas Mafusire¹

Co-author: Andrew Forbes¹

¹ CSIR National Laser Centre

Abstract content (Max 300 words) http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=1&target=_blank **Special Chars**:

We outline a theory for the calculation of the laser beam quality factor of an aberrated laser beam. We provide closed form equations which show that the beam quality factor of an aberrated TEM00 Gaussian beam depends on all primary aberrations except tilt, defocus and x-astigmatism. We extend this concept to defining the mean focal length of an aberrated lens and show that this quantity depends on all Zernike aberrations of ordinal number 0 or 2 except piston. The models are verified experimentally by implementing aberrations as digital holograms in the laboratory. Lastly, we show how the definition of the two concepts may be of use in controlling thermal aberrations in laser resonators using adaptive optics, thereby improving the quality of the beam generated and also reducing the effects of thermal lensing.

Session VII : Imaging and Microscopy / 15

Active spatial polarization control for microscope objectives

Author: Frederik Schaal¹

Co-authors: Christof Pruss¹; Joachim Stumpe²; Michael Jetter³; Michael Rutloh²; Peter Michler³; Susanne Weidenfeld³; Wolfgang Osten¹

¹ Universität Stuttgart, Institut für Technische Optik, Germany

² Universität Potsdam, Institut für Chemie, Germany

³ Universität Stuttgart, Institut für Halbleiteroptik und Funktionelle Grenzflächen, Germany

Corresponding Author: schaal@ito.uni-stuttgart.de

Abstract content (Max 300 words) http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=1&target=_blank **Special Chars**:

We show a micro optical device for non-pixelated active spatial polarization control. The device is based on a photoaddressable material (PAM). The birefringence of the PAM is locally modulated due to the

intensity of the addressing light. This enables the creation of non pixelated spatial polarization patterns with fewer artefacts compared to devices like spatial light modulators.

The optical addressing is done by an integrated micro-optical illumination unit. VCSELs are used as a light source. The addressing patterns are generated by diffractive optical beam shapers. Due to the small size of the components it is possible to realize several addressing channels in one device. By controlling the current of the VCSELs, different illumination patterns can be switched or combined.

The complete system can be integrated into a microscope objective e.g. for switchable phase contrast methods.

16

Biomedical applications of optics

Author: Patience Mthunzi¹

Co-authors: Andrew Forbes²; Jamie Warner³; Kuang He³; Maria Papathanasopoulos⁴; Sandile Ngcobo²; Thulile Khanyile²

¹ CSIR - NLC

² National Laser Center, CSIR

³ Department of Materials, University of Oxford

⁴ Department of Molecular Medicine and Haematology, University of the Witwatersrand Medical School

Corresponding Author: pmthunzi@csir.co.za

Abstract content
(Max 300 words)
Special Chars:

Mammalian cells can be optically micro-manipulated in-vitro to promote embryonic stem cell research, neurodegenerative disorder studies, human immunodeficiency virus (HIV-1) investigations and cancer research science. In this work, lasers of different regimes are employed as they possess special properties that allow classical biomedical applications. Studies toward the interaction of laser light, nanomaterials and biological materials can lead to an understanding of a wealth of disease conditions and result in photonics-based therapies and diagnostic tools. In this talk; firstly, optical transfection and differentiation of embryonic stem cells is presented. Secondly, somatic and dendritic phototransfection of neuroblastoma cells on graphene substrates is shown. Thirdly, using different beam shapes photo-translocation of HIV-1 drugs into TZM-bl cells is given. Finally, optical trapping and sorting of cancerous from healthy ones is demonstrated.

Session III: Wavefront Sensing Techniques / 17

Impact of wavefront aberrations in ultrafast nonlinear optics

Author: Rocío Borrego-Varillas¹

Co-authors: Benjamín Alonso²; Carolina Romero³; Francisco Valle³; Javier R. Vázquez de Aldana⁴; Juan M. Bueno⁵; Luis Roso³; Omel Mendoza-Yero⁶; Íñigo Sola⁷

¹ Universitat Jaume I, Universidad de Salamanca

² Universidad de Salamanca

³ Centro de Láseres Pulsados (CLPU)

⁴ Universidad de Salamanca

⁵ Universidad de Murcia

⁶ *Universitat Jaume I*

⁷ *Universidad de Salamanca*

Corresponding Author: rociobv@usal.es

Abstract content
(Max 300 words)
Special Chars:

Ultraintense femtosecond lasers have become workhorses in disciplines as materials microprocessing, particle acceleration or spectroscopy. Due to the optics inside the cavity and the high-peak-power, wavefront aberrations (WA) are present, degrading the beam quality. The accurate WA measurement and control is therefore essential to get diffraction limit conditions and achieve high peak intensities. In this contribution we present the phase characterization along the chain of a femtosecond laser.

On the other hand, many of their applications originate from the nonlinearities they induce. However, nonlinear processes usually yield significant phase distortions. The effects of WA for experiments in the field of nonlinear optics are also analyzed:

Second-harmonic generation (SHG)

SHG of aberrated pulses is studied in terms of focusability, spatial chirp, beam quality and WA. At high intensities, a phase shift, proportional to the pump beam profile, is induced by the SHG. It is found that in general WAs lead to spatio-spectral coupling and degrade the SH focusability, although under particular conditions they can compensate for the induced phase shift.

Supercontinuum generation (SCG)

We show that diffractive lenses exhibiting strong chromatic aberration can be used for spectral shaping of SCG with femtosecond pulses, obtaining tunable SC pulses and extending the cut-off frequency.

Filamentation

Nowadays, filamentation is commonly used for obtaining shorter pulses. The main constraint of this scheme originates from the existence of an upper energy limit for single filamentation. We demonstrate that astigmatic focusing allows for an increase in the multi-filamentation threshold, consequently improving post-compression.

Electron generation

WA analysis is applied to optimize the experimental setup for electron acceleration in gases and solids. In the first case, it allows for an accurate control of the density of the gas and its dynamics under different experimental conditions, and in the latter it is used as input for a propagation simulation code.

18

Free-motion measurement of the beam propagation factor by means of a spatial light modulator.

Author: Jorge Pérez Vizcaíno¹

Co-authors: Enrique Tajahuerce¹; Jesús Lancis¹; Lluís Martínez León¹; Omel Mendoza Yero¹; Raúl Martínez Cuenca¹

¹ *Universidad Jaume I*

Corresponding Author: jvizcain@uji.es

Abstract content
(Max 300 words)
Special Chars:

The standard ISO/DIS 11146 describes a procedure to measure the beam propagation factor (M^2) by mechanical scanning of the beam waist region. In contrast to this method, we propose a novel experimental implementation where no moving elements are needed.

Our proposal takes advantage of the features of low-cost programmable liquid crystal spatial light modulators (SLMs). A set of lenses with different focal lengths are sequentially encoded in the SLM. Then,

by using a digital sensor at a fixed position, the beam width according to the second order moment of the irradiance is measured for each focal length of the encoded lenses. After fitting the measured data to the theoretical focusing behavior of a real laser beam, the beam propagation factor is obtained.

The use of this kind of modulators introduces some benefits, such as the possibility for high numerical aperture or local beam control of the phase of the lenses which allows for minimizing systematic errors originated by lens aberrations.

The proposed method was successfully validated in the laboratory where a full digital control of the measurement procedure was implemented. The M^2 calculation by this method is very low time-consuming and allows very simple setup. Its application to compact Optics systems is straightforward.

Session IV: Adaptive Control / 19

Multi-conjugated adaptive optics for intense femtosecond lasers

Author: Gilles Cheriaux¹

Co-authors: Nicolas Vedrenne²; vincent Michau²

¹ Laboratoire d'Optique Appliquée

² ONERA-DOTA

Corresponding Author: gilles.cheriaux@ensta.fr

Abstract content (Max 300 words) <http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=28> **Special Chars**:

Many developments since the early 90's have been done on intense laser sources, in order to increase the peak power. Significant progresses were also made to obtain higher and higher average powers. Developments are still on progress especially for systems such as the ILE-Apollon program in France. The various pillars of European ELI programs in the Czech Republic, Romania and Hungary are under construction and target peak power of 10 PW with pulse durations of 15 fs and energy of 150 joules. These lasers are at the state of the art, but many other less powerful systems are now under construction by the institutions themselves or purchased from companies that are Amplitude Technologies and Thales for example. A common requirement to all these systems is to reach highest intensity in the plane of interaction, with applications both on civilian and military side.

To meet these requirements, these intense laser sources require optical components of high quality (reflectivity, flatness and damage threshold) and also of large dimension. Nevertheless despite of these efforts, the intensity on target is degraded by wavefront distortions and energy distribution modifications. This leads to a decreased intensity which is detrimental for the experiment.

Since 2000; efforts have been done by use of one adaptive optic (deformable mirror or DM) and thus correction of the wavefront. This has lead to improve the focused intensity by 30 to 40 %. For achieving this result, the DM shape is derived from the wavefront measurement obtained in the mid-field. This measurement does not take into account the propagation of the beam after the DM and especially the aberrations of the focusing system.

A collaborative French program, ILOOP, between LOA, ONERA and REOSC is aiming to measure the wavefront in the experimental plane and to improve the intensity at focus by the use of more than one adaptive optic in order to shape the energy distribution and the wavefront.

The talk will present the design of the wavefront sensor and first measurement obtained with it. An analysis as a function of the wavelength will also be presented. This point is very important for the femtosecond lasers as the spectrum is lying over 200 nm of spectral bandwidth.

The design of the multi-conjugate loop will be detailed as well as its implementation in a femtosecond laser chain.

Computational Testbench and Flow Chart for Wavefront Sensors

Authors: Davies W. de Lima Monteiro¹; Euller Borges¹; Luciana P. Salles¹; Rafaela Stanigher¹; Úrsula Abecassis²

¹ *Department of Electrical Engineering Universidade Federal de Minas Gerais – UFMG, Brazil*

² *Department of Electronics and Telecommunications, Instituto Federal do Amazonas – IFAM*

Corresponding Author: ue.ursula@gmail.com

Abstract content
(Max 300 words)
Special Chars:

Adaptive Optics is a multidisciplinary topic with a growing number of applications, from ophthalmology to astronomy, each with their respective requirements. There are, to date, many methods, algorithms, components and devices that can be combined in a vast variety of ways for a wavefront-sensor design in Adaptive Optics. There is also an increasing number of didactic books, scientific papers and websites that assist one through the meanders of wavefront sensing, control and actuation. Nevertheless, they often tackle a specific subject or are organized in a sequential structure of general topics, short of displaying in a straightforward fashion how elements can be chosen to work together. Most groups indeed have the knowledge to make suitable decisions, but for a newcomer, the realm of available options is often fuzzy, from device to system level. In this context, we have envisioned a chart that will be useful to aid the visualization of possible choices and how they relate to each other.

We will focus on wavefront sensing and propose a method to display the available options, from wavefront generation to error analysis, aiming to assist in decision making and in organizing a testbench for simulation and optimization of a device or sensing system. This is based on a flow chart branching downwards and laterally, linking together only structurally feasible options. This detector sub-block of an Adaptive Optics system alone features such numerous pathways that we limit ourselves to detail just a few of the possible tracks to illustrate how one can couple simulation codes and tools to design a system and preview its performance. The chart is flexible enough to accommodate new developments on devices and codes. As the chart is communally extended to actuation and control, and its branches are cooperatively populated with simulation models, a more complete mapping of possible systems will result. We will present simulation results that include the effect of several components, including the sampling plane, photodetectors and electronic circuitry on wavefront reconstruction.

Session II : Imaging and Microscopy / 22

High resolution in-vivo imaging of the mouse retina using an adaptive optics system with MEMS segmented piston/tip/tilt deformable mirror.

Author: Robert J. Zawadzki¹

Co-authors: Edward N. Pugh ¹; John S. Werner ¹; Marinko Sarunic ²; Yifan Jian ²

¹ *UC Davis*

² *Simon Fraser University*

Corresponding Author: rjzawadzki@ucdavis.edu

Abstract content
(Max 300 words)
Special Chars:

High resolution in-vivo retinal imaging of small animals is becoming an increasingly important tool in developmental biology and vision science. It is especially attractive for studying temporal changes in animal models of retinal diseases and for monitoring disease progression in response to different risk factors or treatments. To achieve the best possible resolution of retinal structures for precise monitoring and quantification of changes at cellular resolution, one has to measure and compensate for ocular aberrations of the mouse eye over a large pupil. The mouse eye with dilated pupil has a numerical

aperture (NA) 2.5X that of the human eye, enabling the possibility of imaging with optical coherence tomography (OCT) or scanning laser ophthalmoscopy (SLO) at resolutions much higher than available in human eyes.

In our prototype instrument, we used Iris AO adaptive optics (AO) system that includes the PTT111 deformable mirror (with inscribed aperture of 3.5 mm consisting of 37 hexagonal segments and 5 μm stroke (tip/tilt/piston)) and Hartmann-Shack wavefront sensor (WFS) with 37 lenslets, working in a 1:1 optical mapping of DM segments to WFS lenslets. We evaluated performance of this system by measuring and correcting aberrations of the mouse eye. Additionally, images of the microscopic morphology of the retina in-vivo have been acquired with both AO-OCT and AO-SLO modalities. During imaging, mice were anesthetized by inhalation of 2-3% isoflurane delivered in oxygen.

Measurements of the wavefront error from a typical mouse eye with fundus contact lens and the best focus (AO off) was on the order of 200nm RMS error. By activating the AO system, the measured wavefront was reduced to < 50nm RMS error. This corresponds to diffraction-limited imaging as defined by RMS error < $\lambda/14$. Representative images of the mouse retina will be presented. Application of general anesthesia allowed for relatively long imaging sessions of up to 60 minutes without producing adverse effects. Additionally, several measurements of the same animals were performed every other day with no negative effects on the mouse.

Seesion I : AO in Lasers / 24

Recent advances in high-power fundamental mode thin-disk lasers using intra-cavity deformable mirrors

Author: Stefan Piehler¹

Co-authors: Andreas Voss ¹; Birgit Weichelt ¹; Marwan Abdou Ahmed ¹; Thomas Graf ¹

¹ *Institut für Strahlwerkzeuge, Universität Stuttgart*

Corresponding Author: stefan.piehler@ifsw.uni-stuttgart.de

Abstract content
(Max 300 words)
Special Chars:

Thermally induced aberrations are limiting power scaling of solid-state lasers. The concept of the thin-disk laser was developed in order to mitigate this so-called “thermal lensing”. By scaling the gain medium down to a thin disk, a highly efficient back-side cooling scheme can be applied, minimizing the amount of thermally induced aberrations in the pumped laser crystal. This enables the design of high-brightness lasers with a broad dynamic stability range. In fundamental-mode operation, however, the aspherical components of the remaining wavefront distortions arising from the strong temperature gradient at the edge of the pump spot lead to diffraction losses which limit power scalability. These aspherical wavefront distortions can be compensated for by intra-cavity deformable mirrors. For this purpose, we have developed pneumatically deformable mirrors consisting of fused silica substrates with an annular groove applied from the back side. If pressure is applied from the back side of the mirrors, the HR-coated front surface of the mirrors is deformed in a way that closely matches the super-gaussian shape of the aspherical components of the wavefront deformations induced in the thin-disk laser crystal. The magnitude of the deformation is linearly dependent on the applied pressure, which can be controlled very precisely. Hence, the mirror can be accurately tuned in order to effectively compensate for the wavefront deformations generated in the laser crystal at a large range of different pump powers. In recent experiments, we have successfully demonstrated the use of these mirrors in a thin-disk laser resonator. With output powers of up to 815 W from a single disk at close to fundamental-mode operation ($M^2 < 1.4$) reported so far, power scaling beyond the 1 kW is within reach. The results of further experiments currently in progress will be reported during the workshop along with a full characterization of the mirrors

Session IV: Adaptive Control / 25

Characterization and application of a deformable mirror for pulse shaping in the Mid-Infrared

Author: Andrea Cartella¹

Co-authors: Andrea Cavalleri²; Cristian Manzoni³; Giulio Cerullo⁴; Michael Först¹; Stefano Bonora⁵

¹ *Max-Planck Institute for the Structure and Dynamics of Matter, Center for Free Electron Laser Science, University of Hamburg, Luruper Chaussee, 149, 22761 Hamburg, Germany*

² *1Max-Planck Institute for the Structure and Dynamics of Matter, Center for Free Electron Laser Science, University of Hamburg, Luruper Chaussee, 149, 22761 Hamburg, Germany*

³ *CNR-IFN, Piazza L. Da Vinci 32, 20133Milano, Italy*

⁴ *Dipartimento di Fisica - Politecnico di Milano, Piazza L. Da Vinci 32, 20133Milano, Italy*

⁵ *CNR-IFN, LUXOR, via Trasea 7, 35131, Padova, Italy*

Corresponding Author: stefano.bonora@dei.unipd.it

Abstract content
(Max 300 words)
Special Chars:

Deformable mirrors (DMs) can be realized with many technologies. Each of them matches different requirements and have found applications in different specific research fields. The most of the DMs have been designed for the UV or visible or near infrared spectral range which present the wider range of available sources and applications.

Parametric amplifiers have reported successful results in pulse compression in different spectral region from visible to the mid-infrared [Optics Letters 35, 757-759 (2010)]. The mid-infrared (MIR) region is of particular interest because offers unique possibilities to steer the phase state of condensed matter. Selective excitation of low-energy modes, such as lattice vibrations, by intense few-cycle pulses in this spectral range has been shown to control insulator-metal transitions or magnetism in manganites and to induce superconductivity in cuprates. The availability of precisely tailored light pulses may open up new path ways for the control of phase transitions.

Changing the temporal shape of short laser pulses with a given bandwidth requires control of the spectral phase of their electric field. Widely used devices in the near-infrared or visible range, such as acousto-optic or liquid crystals modulators, are not suitable for operation at wavelengths longer than 12 μm : as they require propagation in bulk materials, absorption in this spectral range prevents their use. For this reason, reflective schemes based on deformable mirrors are promising candidates for pulse shaping at these wavelengths. Their spectral coverage is indeed only limited by the reflectivity of their metallic coating.

The DM was designed to operate at the OPA spectral range of about 17 μm . Since the DM stroke has to be comparable with the wavelength this DM gives a maximum stroke of about $\pm 110\mu\text{m}$. We will present the characterization of the DM, carried out with a Moire interferometer and the experimental results of the pulse shaping.

Session II : Imaging and Microscopy / 26

Modal deformable mirror optimization in sensorless Optical Coherence Tomography

Author: Stefano Bonora¹

Co-author: Robert Zawadzki²

¹ *CNR-IFN*

² *Vision Science and Advanced Retinal Imaging Laboratory (VSRI) and Department of Ophthalmology & Vision Science, UC Davis, 4860 Y Street, Ste. 2400, Sacramento, CA 95817, USA*

Corresponding Author: stefano.bonora@dei.unipd.it

Abstract content
(Max 300 words)
Special Chars:

We demonstrated that the modal sensorless correction can be used in Optical Coherence Tomography (OCT) with the use of a modal deformable mirror [Optics Communications, 284(13), 3467-3473 (2011)] exploiting a recent optimization method based on the cancellation of one aberration at a time. This strategy presents many advantages such as the use of few iterations and the absence of local maximum [Opt. Letters, 32(1) (2007)]. Sensorless optimization plays an important role in adaptive optics development thanks to the reduced hardware complexity. The use of sensorless optimization has been demonstrated in some fields such as laser focalization and in the improvement of image quality. In the most of the cases the optimization was carried out by the use of an optimization strategy, such as for example the genetic algorithm or others, which maximizes the value of a merit function which can be either the intensity in the focal spot for the laser optimization case or an image sharpening function in the case of the optimization of an image quality. The Modal Deformable Mirror (MDM) is an electrostatic membrane DM where the actuators are composed by a resistive layer which continuously distributes the electrostatic pressure on the membrane designed in order to directly generate low order aberrations such as defocus, astigmatism, coma and spherical aberration. To test the performance of our Sensorless Adaptive Optics - Optical Coherence Tomography system we tried to improve image quality of the Air Force Test target aberrated by some trial lenses.

Session IV: Adaptive Control / 27

Ultrafast time compensated monochromator with deformable diffraction gratings

Authors: Fabio Frassetto¹; Stefano Bonora²

Co-authors: Caterina Vozzi³; Erika Zanchetta⁴; Gioia Della Giustina⁴; Giovanna Brusatin⁴; Luca Poletto¹; Salvatore Stagira³

¹ National Council for Research of Italy – Institute of Photonics and Nanotechnologies, via Trasea 7, IT-35131 Padova, Italy

² CNR-IFN

³ Politecnico di Milano – Department of Physics and National Council for Research of Italy – Institute of Photonics and Nanotechnologies, p.zza L. Da Vinci 32, IT-20133 Milano, Italy

⁴ Industrial Engineering Department, University of Padova, Via Marzolo 9, 35131 Padova, Italy

Corresponding Author: stefano.bonora@dei.unipd.it

Abstract content
(Max 300 words)
Special Chars:

Active deformable diffraction grating can be used for the realization of a time compensated pulses in the XUV. We present the preliminary tests of time compensation operated in the visible at 800nm. The compensated monochromator consists in a couple of deformable diffraction gratings. The devices consist of a laminar diffractive layer realized by UV lithography that is deposited on the top of a bimorph deformable mirror. The deformable diffraction gratings have been designed to have high optical quality, robustness and compatible with any coating deposition and have only vacuum-compatible materials. We present the characterization of the prototypes in the vacuum ultraviolet and in the visible, showing that the active grating can optimize the beam focusing through its rotation and deformation. Two active gratings have been mounted in a compensated configuration to realize a grazing-incidence time-delay compensated monochromator for high-order laser harmonics. The wavelength selection is performed through the grating rotation, the intermediate slit carries out the spectral selection of a single harmonic and the spectral focusing is maintained by adjusting the grating radii. The instrument has been initially tested in air with a Ti:Sa laser operated at 800 nm. We have been able to demonstrate that the double-grating configuration with active gratings compensates for the pulse front-tilt. The front-tilt given by the first grating is 1 ps and is reduced to 100 fs after the second stage. The final value is limited by the group delay dispersion of the monochromator within the 10-nm bandwidth of the laser centered around 800 nm.

Active gratings may be considered as a cheaper and more flexible alternative to standard gratings for

the realization of extreme-ultraviolet ultrafast monochromators.

Session IV: Adaptive Control / 28

High resolution wavefront control using a photocontrolled deformable mirror in closed loop

Author: Stefano Bonora¹

Co-authors: Antonio Lucianetti ²; Chris Dainty ³; Derek Coburn ³; Jan Pilar ²; Stefania Residori ⁴; Umberto Bertolozzo ⁴

¹ CNR-IFN

² Institute of Physics AS CR, Na Slovance 2, 182 21 Prague, Czech Republic

³ National University of Ireland, Applied Optics Group, Galway, Ireland

⁴ INLN, Université de Nice-Sophia Antipolis, CNRS, Valbonne, France

Corresponding Author: stefano.bonora@dei.unipd.it

Abstract content (Max 300 words) http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=1&target=_blank **Special Chars**:

Using a photocontrolled membrane deformable mirror it is possible to control and correct the wavefront with unprecedented resolution. Our novel design of deformable mirror is an electrostatic membrane mirror actuated through the change of resistivity of a photoconductor substrate rather than using a conventional matrix of electrodes. The Optically addressable Deformable Mirror (ODM) is composed by a Bismuth Silicon Oxide (BSO) photoconductive crystal, and a nitrocellulose metallized membrane. The light pattern which controls the mirror shape is emitted by a commercial DLP projector with 800 x 600 pixels. The main advantages of this device are the extreme reduction of hardware complexity, since just one high voltage line is used and the high resolution addressing of the DM instead of the array of high voltage lines used for standard electrode matrix geometries. We demonstrated those advantages through its use in a closed loop system, by the Zernike characterization exploiting a flexible light addressing up to an equivalent of 15x15 actuators. As a demonstration of the flexibility of use and high spatial resolution of this deformable mirror the mirror has been used as a simulator of atmospheric turbulence and to simulate the design of the ideal deformable mirror for the correction of thermal lensing in high power lasers.

Session VIII : Spatial Light Modulators / 29

All-digital holographic tool for real-time mode excitation and analysis in optical waveguides

Author: Daniel Flamm¹

Co-authors: Andrew Forbes ²; Christian Schulze ¹; Darryl Naidoo ³; Michael Duparré ¹; Siegmund Schroeter ⁴

¹ Institute of Applied Optics, University Jena

² Council for Scientific and Industrial Research, Pretoria and University of KwaZulu-Natal,

³ Council for Scientific and Industrial Research, Pretoria and University of KwaZulu-Natal

⁴ Institute of Photonic Technology, Jena

Corresponding Author: pdm@uni-jena.de

Abstract content
(Max 300 words)
Special Chars:

A real-time procedure for multiplexing and demultiplexing of transversal modes in optical waveguides is presented, based on dynamic and static digital holograms. By using a spatial light modulator (SLM) to encode a digital hologram, the desired complex field is shaped and injected into the waveguide. The SLM's ability to rapidly refresh the encoded transmission function enables one to excite pure single modes, as well as arbitrary coherent mode superpositions, in real-time. The modes leaving the output of the waveguide are subsequently demultiplexed by applying a holographic correlation filter for modal decomposition, thus allowing for an all-digital-hologram approach to modal analysis of wave guiding structures. The working principle is tested using conventional step-index large mode area (LMA) fibers being excited with higher-order single modes as well as superpositions thereof. Extending this approach to a closed-loop-system, enables one to control amplitude- and phase distribution of the emerging optical field.

30

Utilizing speckle decorrelation for tomographic wavefront sensing (with one wavefront sensor)

Author: Nazim Bharmal¹

Co-author: Aglaé Kellerer ¹

¹ *University of Durham*

Corresponding Author: n.a.bharmal@dur.ac.uk

Abstract content
(Max 300 words)
Special Chars:

Generation of speckle using scattering that is spatially incoherent is a common, and often annoying, phenomenon but has not been as yet utilized in adaptive optics for wavefront sensing. This paper describes a method whereby light is scattered from a surface (which may be a plane within a sample being imaged) and then an image is obtained of the speckle created at two defocused planes at some equal but opposite distance from that pupil. Due to the correlation of speckle with propagation, a cross correlation of detected intensity (or amplitude, via interferometric detection) can be used to measure the wavefront gradient. The key advantages of this technique include the ability to alter the sensitivity of the wavefront gradient signal vs. the spatial sampling of the wavefront gradient. A further extension demonstrates how multiple but distinct regions of scattering can be utilized to produce overlapping but mutually uncorrelated speckle. The individual speckle cross-correlation can then be extracted to result in a set of wavefront gradients that, in astronomy, would be described as star-oriented. Astronomical data-reduction approaches can then be used to produce a tomographic or 3D wavefront solution. In this case, the wavefront sensor hardware is no different to the single-scattering source case and the angular source selection is done by computation rather than multiple devices; thus costs and complexity are minimized at the expense of detection and computational time.

Manufacturing and Testing of Unimorph Deformable Mirrors for Space Telescopes

Author: Peter Rausch¹

Co-authors: Sven Verpoort¹; Ulrich Wittrock¹

¹ *University of Applied Sciences Muenster*

Corresponding Author: rausch@fh-muenster.de

Abstract content
(Max 300 words)
Special Chars:

Future concepts of large space telescopes are based on lightweight primary mirrors. These primaries cannot meet the required optical surface figure due to their floppy structure, misalignment of the mirror segments, and gravity release and are likely to generate several microns of wave-front error. One potential solution to correct for these errors could be the integration of a space-compatible deformable mirror. Such a mirror is a prerequisite for a diffraction-limited space telescope with an aperture that is significantly larger than that of the James Webb Space Telescope. A temperature insensitive mirror with suitable diameter, stroke and surface fidelity embodied in the optical train would relax the specifications and improve the optical performance of a space telescope.

The harsh environmental conditions in space impose special challenges on the instruments. A deformable mirror would be exposed to a broad vibration spectrum, as well as to accelerations of several tens of g. Cosmic irradiation may degrade the optical coating, exposure to vacuum could lead to contamination and further degradation of the mirror's surface. Cryogenic temperatures down to 100 K demand a thermally insensitive design of the mechanical support and careful selection of the used materials.

We have scaled our small-sized laser mirror which was originally developed for high power laser applications towards an aperture diameter of 50 mm to take into account the Lagrange invariant of large aperture telescopes. To cope with the cryogenic temperatures, an athermal design was achieved via both CTE matching and stress relieve by implementing an isostatic mounting. The optomechanical layout of the mirror has been investigated by extensive finite element calculations, which allowed for an optimization of the design. The use of low outgassing materials ensures vacuum compatibility.

A tailored test-bed has been designed to experimentally characterize the mirror's performance. To confirm space compatibility, performance tests in a cryogenic environment have been conducted. Further tests were carried out to validate the mirrors ability to withstand vibration, acceleration and irradiation levels typically occurring during space missions.

32

Optical Design and Optimization of Adaptive Automobile Headlight with Liquid Optical Element and Freeform

Author: YiChin Fang¹

¹ *Head of Department*

Corresponding Author: yfang@nkfust.edu.tw

Abstract content
(Max 300 words)
Special Chars:

This research proposed a new optical design concept of advanced Mechanical Adaptive Steering Automobile Headlight System in order to tune up light efficiency, reduce volumetric size and the most important, get rid of complicated mechanical system. All research are mainly focus on (1) Optical Design of Freeform Surface technology.(2) Image technology of DMD . (3) Human Vision characteristic .(4) Digital Signal Processing and its application with GPS

Traditionally Automotive headlight employ a plate to create the light shape, which meet the rule of road safety, According to our new design, no more plate is required. Therefore, great improvement of light efficiency will be expected up to 30%, Besides, volumetric size will be further reduced. More details,

please refer to “Optical design of automotive headlight system incorporating digital micromirror device,” APPLIED OPTICS, Vol. 49 No. 22(SCI), 2010, pp.4182~4187” .

First year, we mainly study optical design of advanced LED automotive headlight design and optimization with assistance of freeform surface. New concept of optical design with DMD might greatly reduce volumetric size of headlight system,

In second year, individual human vision characteristic will be considered as a part of automotive headlight system in my research in order to improve safety of road drive. Many experimental work and simulation analysis will be studied and compared in order to achieve best performance of automotive headlight system according to human vision.

In third year, GPS will be optimized with DMD and infrared image from cameras in the car in order to achieve best performance during extremely driving situation. All are based on research of first and second year, optical design and human vision characteristic. With assistance of GPS and night vision camera, all road data will be fast optimized according to human characteristic of individual driver. Then DMD will deliver the best-projected illumination for driver during extremely situation.

Keyword: light efficiency DMD Human Vision GPS Digital Signal Processing Freeform surface

34

Compensation of the two-stage phase-shifting algorithms with respect to detuning and harmonics

Author: Daniel Malacara-Doblado¹

Co-authors: Alejandro Tellez-Quinones²; Jorge Luis Garcia-Marquez¹

¹ Centro de Investigaciones en Optica, A. C.

² Instituto Politecnico Nacional

Corresponding Author: dmalacdo@cio.mx

Abstract content (Max 300 words) <http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=28> target="_blank">Special Chars:

The study of two-stage phase-shifting algorithms is a topic of recent research, specially the Fourier analysis of these algorithms with respect to insensitivity properties to various error sources. The main motivation of this paper is to propose two-stage phase-shifting algorithms with insensitivity properties to detuning and harmonics for the two sets of interferograms with different or equal reference frequencies.

In this work the design of two-stage phase-shifting algorithms is based on the development of generalized equations that consider non-constant phase shifts. The analysis of the frequency sampling functions representing these algorithms is also considered.

Session VII : Imaging and Microscopy / 35

Correction for distortions in holographic nanointerferometers

Author: Vladimir Venediktov¹

Co-authors: Irina Pasechnik¹; Sergey Pul'kin¹

¹ *St.-Petersburg State University*

Corresponding Author: vlad.venediktov@mail.ru

Abstract content
(Max 300 words)
Special Chars:

Fast progress in matrix liquid-crystal phase modulators, in particular those of Holoeye production, made it possible to realize some interesting schemes in holography, and, in particular, in holographic interferometry for investigation of nano-sized objects. Combination of analogous and digital processing made it possible, in particular, to provide the real-time magnification of holograms and real-time digital variation of spatial frequency of interferogram. However, when considering the nano-size objects, even in a high optical quality interferometer one has to keep in mind the residual distortions of the interfering wavefronts, imposed by residual defects and deformations of the interferometer elements. One can eliminate these distortions by combining in one and the same scheme of the real-time holographic magnification of interferogram and of the dynamic holographic correction for distortions. We discuss the results of theoretical evaluation of such a combined interferometer performance and of its experimental simulation.

Session V: AO Techniques / 36

Adaptive Lenses for Displays & Vision

Author: Gordon Love¹

¹ *Durham University*

Corresponding Author: g.d.love@durham.ac.uk

Abstract content
(Max 300 words)
Special Chars:

There are a whole host of technologies for producing lenses with controllable focal lengths, ranging from electro-wetting to liquid crystal technology. In this paper we will discuss some of our recent work on applying liquid crystal lenses to applications in 3D displays and vision science. For these applications we typically need very fast lenses and we shall also discuss the background technology of switchable birefringent ferroelectric liquid crystal lenses.

Session V: AO Techniques / 37

Results on the high power testing of screen-printed deformable mirrors

Author: Claudia Reinlein¹

Co-authors: Matthias Goy ¹; Michael Appelfelder ¹

¹ *Fraunhofer IOF, Jena*

Corresponding Author: claudia.reinlein@iof.fraunhofer.de

Abstract content
(Max 300 words)
Special Chars:

The performance of high power laser systems is affected thermal lensing. Deformable mirrors have been applied for the compensation of these thermal lensing effects. Difficulties can arise as not only

the optical properties of lenses and mirrors in the beam path are affected by thermal lensing, but also deformable mirrors itself. The radiation of a high power laser beam is partly absorbed by the deformable mirror surface and transferred into heat. Mirrors temperature is increased leading to laser-induced mirror deformations. These deformations need to be analyzed to evaluate the applicability of a deformable mirror in high power systems. This paper gives results on the high power testing of our MOEMS screen-printed deformable mirrors.

We introduce the measurement set-up based on a 1 kW laser beam that is incident on the deformable mirror. The deformable mirror is equipped with a dielectric coating that offers a reflectivity of 99.4 % at 1070 nm in order to allow for the application in high power systems. The high power laser beam is expanded to a diameter of 20 mm to match the mirror's aperture. Subsequently, the beam is compressed to the wavefront sensor's aperture to measure the laser-induced aberrations. We measure the overall laser-induced mirror deformation and also give results on their temporal behavior. The laser-induced mirror deformation is only few micrometers in case of 1 kW laser load.

The design of the deformable mirror allows for a compensation of the laser-induced deformations by mirror heating. The temperature-induced deformation rate is $-1\mu\text{m/K}$. In the next step, we demonstrate the further minimization of the laser-induced deformations by mirror heating and demonstrate the applicability of the screen-printed deformable mirror for high power applications.

Session VII : Imaging and Microscopy / 38

Advances in adaptive optics nonlinear microscopy for applications in medical and life sciences

Author: Juan M. Bueno¹

¹ *Universidad de Murcia*

Corresponding Author: bueno@um.es

Abstract content
(Max 300 words)
Special Chars:

In the last years, the combination of imaging microscopy and ultrafast laser sources to produce non-linear signals has opened new research opportunities in Biology and Biomedicine. In nonlinear (multiphoton) microscopy two infrared photons are simultaneously absorbed by the tissue and one visible is emitted. Two-Photon Excitation Fluorescence (TPEF) and Second-Harmonic Generation (SHG) are well-established non-invasive methods used for imaging and mapping sub-cellular biological structures. This technique is auto-confocal, provides intrinsic optical sectioning and allows 3D analysis and volume rendering. However, multiphoton imaging is also affected by aberrations (laser beam, microscope optics and specimen itself). These reduce the quality of images, in particular those corresponding to deeper planes within the sample. In our lab, a custom-made multiphoton microscope combined with adaptive optics (AO) devices has been developed to improve multiphoton imaging of biological tissues, in particular those of the eye. A deformable mirror with a Hartmann-Shack sensor (working in closed-loop), and a liquid-crystal spatial light modulator (in sensor-less mode) have been used to investigate the effects of aberrations when visualizing corneal and retinal structures. Along this presentation the last advances in AO multiphoton imaging, both TPEF and SHG, will be shown. AO techniques revealed ocular features never seen before without using fixation or staining procedures. Multiphoton image quality was improved independently of the depth location of the imaged plane. It will be also shown how that deeper the imaged structure the more influence of higher order aberration terms. The influence of the field-of-view and the order of the Zernike modes in a modal correction will be also explored. Finally, different algorithms and image quality metrics used to optimize the final image will be also compared.

Session X: Propagation and Turbulance / 39

Adaptive Optics for Horizontal Propagation Applications

Author: Sergio Restaino¹

Co-authors: Jonathan Andrews¹; Ty Martinez¹; Wilcox Christopher¹

¹ *Naval Research Laboratory, Remote Sensing Division*

Corresponding Author: sergio.restaino@nrl.navy.mil

Abstract content
(Max 300 words)
Special Chars:

Adaptive Optics (AO) is a well proven technology for imaging systems used for astronomical and Space Surveillance applications. However, the application of these proven techniques to horizontal path imagery is not straightforward, and so far has not been investigated for imaging systems. There are two major problems with extending AO systems for vertical imaging systems to horizontal imaging regime. First, the optical effects of atmospheric turbulence are far more severe for horizontal than for vertical paths. Furthermore, there is now growing experimental evidence that in the horizontal regime the usual wavelength scaling of the strength of turbulence does not hold. This is readily apparent from observing the slight effect of twinkling of stars compared to the pronounced shimmering of objects when viewed across a hot pavement. . Second, horizontal imaging systems generally involve viewing extended sources over relatively large fields of view. Currently no wavefront sensing schemes exist for this application. Primarily for these reasons, the development of an AO system for horizontal imaging systems remains an important unsolved DoD problem. In this paper we will present results and analysis related to our horizontal path imaging and correction effort.

Session VI: Vision / 41

Dynamic generation of scattering for high resolution adaptive optics in the eye

Author: Enrique-Josua Fernandez¹

Co-authors: Augusto Arias¹; Pablo Artal¹

¹ *Universidad de Murcia*

Corresponding Author: enriquej@um.es

Abstract content
(Max 300 words)
Special Chars:

Adaptive optics (AO) is benefiting a number of different fields. In the particular case of ophthalmic applications, the correction of the aberrations of the eye permits to image the retina with unprecedented level of detail, unveiling the subtle structures of individual cells. On the other hand, the controlled manipulation of the wavefront accomplished by AO visual analyzers allows a better understanding of the impact of eye's aberrations in vision. However, aberrations are not the only limiting factor for both vision and retinal imaging. Normal young eyes also exhibit moderate amounts of scattering which can degrade the optical quality of retinal images. Scattering is known to dramatically increase with age. Adaptive optics may have the potential of eventually removing some scattering, through high spatial frequency correctors. Liquid crystal devices can incorporate resolutions of up to 2 million of independent pixels for scattering compensation, being ideal candidates for such applications. Time reversal experiments demonstrating the practical compensation of scattering have been already reported under controlled situations in microscopy. In this direction, a reliable experimental eye model would be advantageous for the progress of the technique, before its real time demonstration in the living eye. The eye model is necessary for demonstrating the double-pass implementation of scattering compensation, and the subsequent refining of algorithms for real time operation. We have developed a relative simple eye model to mimics the optics of the eye, and includes a transmissive liquid crystal spatial light modulator for scattering control (LC 2002, Holoeye Photonics AG, Germany). The latter can be programmed to different configurations in real time producing different levels of scattering. The scattering can be generated by mostly phase modulation, or with different combinations of amplitude and phase. Double pass images obtained from the model resemble those obtained in real eyes with high levels of scattering.

The experimental eye model is an important tool for the development of the next generation ophthalmic adaptive optics systems capable for both wavefront and scattering manipulation in the living eye.

Session VIII : Spatial Light Modulators / 42

Phase generation in white light with a 6-Pi Liquid Crystal on Silicon (LCoS) device

Author: Pedro Prieto¹

Co-authors: Emmanuel Chirre¹; Enrique Josua Fernandez¹; Pablo Artal¹

¹ *Lab Optica, IUI Optica y Nanofisica, U Murcia*

Corresponding Author: pegrito@um.es

Abstract content
(Max 300 words)
Special Chars:

Phase modulators based on liquid crystal are currently applied in many fields. The development of Liquid Crystal on Silicon (LCoS) technology has notably improved the performance of these devices. Analyzing vision with Adaptive Optics is one of the new applications taking advantage from these gadgets. In Vision Analysis procedures, subjects undergo visual testing through modified aberration patterns, controlled and manipulated by the operator. Some of the typical drawbacks of liquid crystals, such as slow response or diffraction losses, have been significantly reduced in LCoS devices but they are still present to some extent and can be relevant, especially when large aberrations are involved. This is typically the case for the eye, even in normal subjects, when low order terms are included. Therefore, there is a continued interest to produce enhanced devices. In this context, we present results for a new LCoS device capable for 6Pi modulation (Holoeye Photonics AG, Germany), comparing performance to that of a regular 2Pi LCoS. An experimental setup was built incorporating the two modulators, so that simultaneous operation and comparison could be performed, a Hartmann-Shack wavefront sensor and a camera for experimental point spread function (PSF) recording. Measurements were taken using a laser source and a tuned spectrum provided by a thermal source coupled to a liquid crystal tunable filter. The 6Pi modulator showed slightly slower temporal response than the standard 2Pi device, but still in the useful range for visual applications. Comparison between monochromatic PSFs showed similar fidelity for both devices, but diffraction effects were less marked in the 6Pi device. Wavefront measurements for different wavelengths showed less than 10% variation across the visible spectrum for the 2Pi modulator and less than 7% for the 6Pi device. In either case, this means a small chromatic degradation, especially when compared to the eye's natural chromatic aberration. In conclusion, the new 6Pi device has the potential for reducing the diffraction ghost produced by phase wrapping, in addition presenting lower chromatic dispersion than the 2Pi device. These features are particularly interesting for Vision Analysis applications, where subjects perform visual testing, typically in white light, through modified phase masks generated by an LCoS spatial light modulator.

43

A parametric study of the contributing factors influencing femtosecond pulse shape transfer via difference frequency mixing.

Author: Nicolene Botha¹

Co-authors: Hermann Uys¹; Lourens Botha¹

¹ *NLC*

Corresponding Author: gnicbotha@gmail.com

Abstract content
(Max 300 words)
Special Chars:

Shaped femtosecond pulses in the far infrared (IR) regime are required for various processes. However, current shaping techniques are limited to the visible and the near infrared. Difference frequency conversion is one method that can be used to transfer shaped pulses from the visible and the near infrared to the far infrared, however, the fidelity of the transfer process and the factors influencing the fidelity is not clear. In this paper difference frequency mixing (DFM) of shaped femtosecond pulses in non-linear crystals is simulated, the transfer of the shaped pulses to the far infrared wavelength is investigated and factors are identified that have an influence on the transfer fidelity. Difference frequency generated pulses, using a non linear crystal, is generated in the laboratory and measured for different double pulse separations and the transfer efficiency is investigated.

Session V: AO Techniques / 44

Design optimization of an actuator pattern for a unimorph deformable mirror

Author: Michael Appelfelder¹

Co-authors: Andreas Tünnermann²; Claudia Reinlein²; Erik Beckert²; Ramona Eberhardt²

¹ Friedrich Schiller Univ. of Jena, Inst. of App. Physics

² Fraunhofer Inst. for Applied Optics and Precision Engineering

Corresponding Author: michael.appelfelder@iof.fraunhofer.de

Abstract content
(Max 300 words)
Special Chars:

For a high order correction of laser beams usually a deformable mirror (DM) is used. A lot of different concepts exist for the design of these mirrors. Especially unimorph deformable mirrors feature low cost, low power consumption and a high stroke capability for the correction of large wave front aberrations. Additionally our approach is using technologies based on wafer level manufacturing of ceramic substrate materials which potentially leads to low cost deformable mirrors.

The optical performance of a DM is commonly stated by the capability to reproduce Zernike polynomials with respect to the amplitude and the precision of the individual coefficients. These values are determined by the actuator pattern of the DM. A pre-optimization of electrode patterns which was used as an input for finite element analysis (FEA) has been done. This pre-optimization was done with the help of the symmetry properties of the Zernike polynomials, adapted to our fixed edge mirror mount boundary condition. For the verification of the FEA model, the computed values have been compared to an analytical model. A high agreement between these values has been found. The deflection shapes for each individual actuator were calculated with the FEA software CoventorWare.

The result was the maximum adjustable Zernike coefficients which can be represented with the deformable mirror. Also the precision, indicated by the RMS error and the purity have been evaluated. We've computed these values for five different actuator layouts. Based on the results two actuator patterns with 41 actuators, consisting of 40 actuators located in the middle and one outer actuator ring have been selected. With the inner 40 actuators a concave deformation can be achieved. While applying a voltage to the outer actuator, the mirror deforms convex. This effect can be used for increasing the working range of a deformable mirror.

Furthermore the electrical contacting of the actuators has been optimized. A reduction of the feed lines dimensions for contacting the actuators with the contact pads located at the rim has been achieved. These contact pads were used for a global electrical connection of the DM. A larger and a more uniform deflection of the actuators is expected.

First measurement results obtained with these mirrors are also presented and are compared to the values obtained by the optimization process.

Session V: AO Techniques / 45

Large Scale Deformable Mirror Based on Bimorph and Stack Actuators

Author: Vadim Samarkin¹

Co-authors: Aleksey Rukosuev¹; Alexander Alexandrov¹; Alexis Kudryashov¹

¹ *Active Optics NightN Ltd.*

Corresponding Author: samarkin@nightn.ru

Abstract content
(Max 300 words)
Special Chars:

Main element of any adaptive optical system is the corrector which determines the properties and ability of the system. The bimorph deformable mirror (DM) is intended to reproduce and thus correct for low order aberrations [1]. Such mirrors have large deformation stroke (up to 100 microns), wide dynamic range (up to several kHz), ability to hold the intensities up to 20 J/cm² for pulsed beam and up to 50 kW/cm² for CW radiation and the possibility to correct for the low-order aberrations by small number of actuators.

Aperture for bimorph DM up to 150 mm is usual now. The 180 mm bimorph DM showed good performance of the wavefront correction in laser systems with sub PW level of intensity [2]. But some applications need the DMs of far bigger sizes (about 500 mm), for example, when it substitutes for the final mirror in multi cascade laser system. As the big bimorph DM is rather thin, the surface shape is usually not perfect and stable. We propose the design of large scale DM using both PZT bimorph and stack actuator technologies. The stacks actuators support the DM and allow to change and correct for the surface shape either by open and/or closed loop control.

The results of study of the prototype of such DM will be presented. The DM size was 220 x 220 mm, the thickness was 4 mm, the ratio thickness to aperture was 1/55. Number of bimorph electrodes was 60. Bimorph type DM was glued on the tops of stack actuators. The stacks are arranged on the thick glass base and supported mirror at the periphery outside of the bimorph electrodes. The number of stacks was 12. Initial surface parameters were PV = 19 μ, RMS = 3.4 μ. Part of these aberrations has been introduced by gluing of stack actuators. Correction of the surface by using of 12 stacks actuators only gave us the surface quality PV = 2.6 μ and RMS = 0.3 μ. In the second step this surface was perfectly flattened by all 60 bimorph electrodes to the quality PV = 0.25 μ and RMS = 0.038 μ that was about λ/30.

[1] A.Kudryashov, V.Shmalhausen, *Opt. Eng.*, vol. 35(11), 3064 (1996).

[2] A.Alexandrov, V.Zavalova, A.Kudryashov et al., *LEI2009 Proc. of the Conference*, Brasov, Romania, 16-21 October 2009, Editor D.Dumitras, 123 (2010).

46

Wide field wavefront sensing on extended scenes and possible applications

Author: Roberto Ragazzoni¹

¹ *INAF - Astronomical Observatory of Padova - Italy*

Corresponding Author: roberto.ragazzoni@oapd.inaf.it

Abstract content
(Max 300 words)
Special Chars:

Multi Conjugated or Multi Object (that translates into Multi Zonal in several possible industrial and medical applications) Adaptive Optics requires wavefront sensing over an extended scenes for complex objects that span much more than the isoplanatic patch. Whenever the scenery is complex the number

of pixel requested for a Shack-Hartmann like application (or whenever the wavefront sensor detects on the focal plane) can easily approach untreatable figures. I propose to use a pupil plane wavefront sensing in which an intermediate filter is located in the focal plane and that has to be adjusted by the signal collected by an auxiliary detector looking through the whole aperture to the scene and hence conjugated to the focal plane while the gain of the signal per each subaperture will be given by a tip-tilt modulation introduced artificially in the wavefront sensing channel.

This approach takes, to some extent, advantage from the sharpening of the image and can handle a slowly changing scenery.

The possible applications of this approach to medical and strategic imaging are briefly reviewed.

47

Localization and image reconstruction of inclusions embedded in biological tissue (turbid media) by means of adaptive optical system

Author: Ilya Galaktionov¹

Co-author: Alexis Kudryashov²

¹ *Student*

² *Head of laboratory*

Corresponding Author: ilya_galaktionov@activeoptics.ru

Abstract content
(Max 300 words)
Special Chars:

Localization of alien inclusions embedded in near-surface layers of tissue and noninvasive parameter reconstruction of biological tissue structure elements in the normal and in the diseased state are important biological and medical tasks. Information about the light-scattering and absorption properties of tissue is necessary for both diagnostic and therapeutic methods, such as laser-induced fluorescence to diagnose malignant tissue and laser-induced hyperthermia and photodynamic therapy to treat diseased biological tissue.

The aim of this work is image reconstruction of inclusions, embedded in turbid media. To improve image quality we used well known effect called «coherent backscattering». This effect is the sharp increase of backscattered light intensity in the opposite direction to the incident beam and is observed, when coherent light propagates through turbid media. Therefore, since the backscattered light is still coherent, we can consider its phase (or, to be more precise – some averaged phase) and thus we can use adaptive optical system to detect and recognize the investigated object.

In our experiments we used adaptive optical system that consists of bimorph deformable mirror and Shack-Hartmann wavefront sensor. The principle of its work is the following: the turbid media is radiated with collimated laser beam. Some part of the light is absorbed, other part is scattered in all directions, including the reverse. Then we measured the current phase distribution of the backscattered light by means of wavefront sensor. And after this, according to the phase distribution information, we applied phase conjugation algorithm to compensate for existing wavefront aberrations using deformable mirror.

The use of adaptive optical system together with image reconstruction applying Wiener filter resulted in almost ten time increase of the measure of image sharpness.

Real-time high speed adaptive optical system for imaging and laser beam control

Author: Alexis Kudryashov¹

Co-authors: Alexander Nikitin²; Alexey Rukosuev³; Vadim Samarkin³

¹ *Head of the Lab*

² *Researcher*

³ *Senior Researcher*

Corresponding Author: kud@activeoptics.ru

Abstract content
(Max 300 words)
Special Chars:

In this paper we consider the low-cost high-speed adaptive optical system to be used for a real-time turbulence correction. It consists of standard, high-speed (up to 2 kHz frame rate) Shack-Hartmann wavefront sensor, electronics, software and ... stacked actuator deformable mirror. We discuss the advantages and disadvantages of the use of such a correctors compare to standard bimorph mirrors. Also, various algorithms of correction are considered. We suggest to use simple phase conjugation method to obtain the best speed result. Though, for better correction simple hill-climbing approach would be preferable. Timing diagrams of correction are presented and discussed. Important question – how fast should be adaptive system if we want to compensate turbulence changing with the frequency f is considered. As a result – we built the adaptive system that can compensate for real-time aberrations with the closed-loop frequency of 200 Hz. The amplitude of corrected aberrations is in the range of $\pm 1.5 \mu$ (local wavefront distortions). Maximum phase aberrations could be compensated are up to 8μ .

49

Artificial model of human eye aberrations proceeded in real-time

Author: Anna Lylova¹

Co-author: Alexis Kudryashov²

¹ *Student*

² *Head of laboratory*

Corresponding Author: ann_lylova@activeoptics.ru

Abstract content
(Max 300 words)
Special Chars:

Human eye is non-ideal optical system. Cornea, lens and vitreous body are sources of optical aberrations. There are several medical tasks where the precise measurements of aberrations is important, for example, excimer laser vision correction, clinical diagnosis of the retina etc.

In fact, real human eye aberrations are not static because of various factors, such as state changing of tear film, fluctuations accommodations, etc.

By now many investigations aimed on high accuracy human eye modeling techniques exist. However, dynamics of phase distortions is not studied in these works.

In our work for human eye model reconstruction an open adaptive optical system including wavefront sensor (Shack-Hartmann type) and wavefront corrector (flexible mirror) was used. The principle of system working is following: we got the information about wavefront shape presented by vector of Zernike coefficients (from a standard aberrometer). As all known the basic aberrations of human eye are of course low-order aberrations like defocus, astigmatism, coma, spherical aberration. And thus it is suitable to use deformable mirror with modal response function of actuators in order to reproduce these

low-order aberrations. So in our work we applied bimorph deformable mirror. This kind of wavefront corrector can easily reproduce first 15-25 Zernike polynomials. To model wavefront profile we simply calculate and apply control voltages to our bimorph mirror electrodes.

That need to be account during real-time reproduction of the artificial human eye wavefront. The time of deformable mirror response also has an influence on system dynamics.

In our case in experiment the frequency of aberrations modeling is similar to the human eye aberrations (5-25 Hz). So we are able to say that our model of phase distortions reconstruction is real-time.

Session V: AO Techniques / 50

Recent Advances in MEMS Deformable Mirror Technology

Author: paul bierden¹

¹ *boston micromachines*

Corresponding Author: pab@bostonmicromachines.com

Abstract content
(Max 300 words)
Special Chars:

With the continual expansion in the use of adaptive optics in the fields of biological imaging, ophthalmic instrumentation and laser communication, the demands on the wavefront corrector has also continued to grow. This paper will describe the design, manufacture, and testing results of the latest generation of optical quality micromachined deformable mirrors (DMs) that have been manufactured to meet these needs. We will also discuss the latest in the area of packaging and high voltage drive electronics to make the MEMS DMs more easily integrated into advanced research operations. Finally, new test procedures and modeling of these devices for open loop operation will be presented.

Session II : Imaging and Microscopy / 51

Superpenetration Multiphoton Microscopy Enabled Through MEMS DM Technology

Author: paul bierden¹

¹ *boston micromachines*

Corresponding Author: pab@bostonmicromachines.com

Abstract content
(Max 300 words)
Special Chars:

Paul Bierden¹, Steven Cornelissen¹, Thomas Bifano^{1,2}, Hari Paudel², John Taranto³, Ben Potsaid³

¹ Boston Micromachines Corporation, 30 Spinelli Place, Cambridge, MA 02138

² Department of Mechanical Engineering, Boston University, 110 Cummington St. Boston, Massachusetts 02215, USA

³ Thorlabs Inc, 56 Sparta Avenue, Newton, New Jersey 07860 pab@bostonmicromachines.com

This paper will discuss the development and demonstration of a superpenetration multiphoton microscope (S-MPM) that will more than double the imaging depth achievable in highly scattering biological tissue. MPM technology has revolutionized the field of subsurface biological imaging, but its depth of penetration is limited. The severe scattering introduced by biological tissue – especially neural tissue – prevents most commercial MPM instruments imaging beyond a few scattering mean free paths. With

this limitation, research on cells and cell networks at the frontier of neuroscience is constrained. A recent breakthrough in coherent light propagation and control through highly scattering media demonstrated the possibility of enhancing focal intensity by factors of several hundred on the far side of a medium, despite any amount of scattering, by using a spatial light modulator to modify the phase of the coherent light on the near side of the medium. In this paper we will discuss the combination of MPM and BMC's fast microelectromechanical spatial light modulators (MEMS SLMs) to offer a compelling way to exploit this breakthrough in optical science that will make a substantial impact on biomedical and neurobiological research.

Session VIII : Spatial Light Modulators / 52

A novel technique to generate and temporally shape multiple pulsed laser beams using 2D-SLMs

Author: Dirk-Mathys Spangenberg¹

Co-authors: Erich Rohwer²; Pieter Neetling²

¹ *University of Stellenbosch*

² *Stellenbosch University*

Corresponding Author: dirk.spangenberg@gmail.com

Abstract content
(Max 300 words)
Special Chars:

It has been shown that a two dimensional phase only spatial light modulator (SLM) can be used to do arbitrary temporal beam shaping. This is significant because the transfer function in general requires both amplitude and phase modulation to be applied to the spectrum of a laser pulse. The amplitude and phase modulation is implemented using blazed gratings in a specific configuration to affect spectral shaping. We build on this technique by introducing the ability to split the input light beam into multiple beams with another 2D SLM at the input. Each individual beam can now be temporally shaped using the same spectral shaping technique and a single 2D SLM in a standard 4f geometry in combination with the appropriate gratings. We further show how the central wavelength of the beams can be off-set linearly with respect to each other, allowing each beam to have its own central wavelength. This technique has applications in high power physics where lasers with ultra short pulses and ultra high instantaneous power are used to selectively excite and probe specific energy level transitions, which in turn has application in coherent control as well as fluorescence microscopy.

Session II : Imaging and Microscopy / 59

ADAPTIVE OPTICS FROM MICROSCOPY TO NANOSCOPY

Author: Booth Martin¹

¹ *University of Oxford*

Corresponding Author: martin.booth@eng.ox.ac.uk

Abstract content
(Max 300 words)
Special Chars:

High resolution microscopy relies on the use of high quality optics with the goal of obtaining diffraction-limited operation, working at the physical limits imposed by the wavelength of the light. Yet in many cases this goal is not achieved as aberrations, distortions in the optical wavefront, blur the focus and

reduce the resolution of the system. Aberrations can arise from imperfections in the optics, but are often introduced by the specimen, particularly when imaging thick specimens. One common source is a planar mismatch in refractive index, such as that between the microscope coverslip and the specimen mounting medium, which introduces spherical aberration. Biological specimens also exhibit variations in refractive index that arise from the three-dimensional nature of cells and tissue structures. In general, these aberrations become greater in magnitude and more complex in form as the focusing depth is increased. The induced wavefront aberrations distort the focus causing a reduction in resolution and, often more importantly, reduced signal level and contrast. These effects limit the observable part of the specimen to a region near the surface.

Adaptive optics systems enable the dynamic correction of aberrations through the reconfiguration of an adaptive optical element, for example a deformable mirror or liquid crystal spatial light modulator. Adaptive optics was originally introduced to compensate for the optical effects of atmospheric turbulence on telescope imaging. The overall operation is based upon the principle of phase conjugation: the correction element introduces an equal but opposite phase aberration to that present in the optical system. As the sum of these two aberrations is zero, diffraction limited operation should be restored. Various adaptive schemes have been developed for a range of different modalities including confocal, multiphoton and widefield microscopes. We review the methods and applications of these systems in biological and other areas. We also present recent developments in adaptive optical methods for super-resolution nanoscopy. In particular, this includes new image-based adaptive schemes for stimulated emission depletion (STED) microscopy.

60

Free space prof without Free Space

Session X: Propagation and Turbulence / 61

Free Space prop without the free space

62

re

Session VIII : Spatial Light Modulators / 63

Shaping ultrafast pulsed beams in space and time with programmable spatial light modulators

Author: JESUS LANCIS¹

Co-authors: Gladys Minguez-Vega ¹; Jorge Pérez-Vizcaino ¹; Omel Mendoza-Yero ¹

¹ *Universitat Jaume I*

Corresponding Author: lancis@uji.es

Abstract content
(Max 300 words)
Special Chars:

Laser pulses in the femtosecond time scale are indispensable tools in many scientific and technological disciplines. These ultrashort pulses provide unique temporal resolutions for understanding of phenomena that develop in a comparable time range. Also, optical energy squeezed into such short time window yield enormous high peak powers and intensities, paving the way to generate unprecedented interactions of light with matter and triggering a new scenario for applications in the world of photonics. However, ultrashort pulses are extremely elusive and are more unforgiving of imperfections in optical systems as compared to ordinary incoherent broadband light sources. Wave front control and correction, as well as pulse shaping, is crucial in order to be able to manipulate the ultrashort pulse in an optimal, reproducible and well-defined way and to obtain ultimate performances for ultrashort laser facilities.

On the other hand, advances in spatial light modulation enable fine control of the amplitude, the phase, and/or the polarization of the light field at the micron scale. By merging the two realms, in this talk we will demonstrate pulsed laser beams with intriguing spatial and temporal waveforms by shaping the laser output by using a liquid crystal spatial light modulator.

Session I : AO in Lasers / 64

Achieving the highest intensity from the Orion Laser Facility

Author: Nicholas Hopps¹

¹ AWE plc

Corresponding Author: nick.hopps@gmail.com

Abstract content
(Max 300 words)
Special Chars:

The Orion Laser Facility at AWE in the UK is a recently commissioned, multi-kilojoule laser facility for the study of high energy density plasma physics. It consists of ten “long pulse” beamlines, which each deliver 500 J at 351 nm and two “short pulse beams”, each capable of 500 J pulses in 0.5 ps at 1054 nm.

The long pulse beams usually operate with continuous phase plates to deliver a user-defined focal profile, albeit at many times the diffraction limit. The need for wavefront correction is therefore limited to system operability issues.

The short pulse beams utilise the chirped pulse amplification scheme to deliver power in excess of 1 petawatt to target. Experiments also usually require the highest possible focal intensity – greater than 10^{21} Wcm^{-2} has been inferred from measurements. Adaptive optics systems are of crucial importance in achieving this goal. Each short pulse beamline is fitted with a 63 element monomorph mirror and a wavefront sensor at the end of the amplifier chain. However, further downstream optics, such as the pulse compression gratings and final focussing mirror, produce aberrations and these must also be controlled.

An overview of the facility will be given for context. The main theme of the talk will be a detailed discussion of the sources of aberration and the challenges faced and overcome in delivering the highest intensity on target.

Session X: Propagation and Turbulance / 65

Quantum Communications along Optical Links with Strong Turbulence

Author: Villoresi Paolo¹

Co-author: Ivan Capraro, Davide Bacco, Alberto Dall'Arche, Davide Marangon, Francesca Gerlin, Andrea Tomaello, Giuseppe Vallone

¹ *Department of Information Engineering, University of Padova,*

Abstract content
(Max 300 words)
Special Chars:

The free space propagation of photonic qubits is one of the most intriguing and novel subjects, in which Quantum Physics provides the paradigm for a leap forward in Communications. However, quantum protocols as teleportation, quantum-key-distribution and entanglement swapping along free-space and satellite links are entwined with beam degradation due to turbulence [1–3], seriously hampering the quantum-bit-rates and the immunity from background noise. For instance, in QKD the quantum state that is prepared and sent at the transmitter side experiences a transformation in the spatial spectrum in addition to the vacuum diffraction, that requires strategies to be compensated.

We report in a series of experiments in which the turbulence is probed and the possible countermeasures, including the use of Adaptive Optics, is investigated. The longest link was chosen between the Optical Ground Station (OGS) of the European Space Agency (ESA), in Tenerife and the Jakobus Kapteyn Telescope (JKT) in La Palma, at the Canary archipelago, separated by about 143 km, both at the altitude of about 2400 m above the Atlantic Ocean. The level of losses is in the range of what expected in the Space-to-ground links, while the effects of turbulence are supposedly larger.

We have realized the link using a optimized refracting transmitter, whose key component is a singlet aspheric lens of 23 cm diameter with $f/10$ aperture [4]. The choice of the lens aims to minimize the spot size at OGS compared to the telescope primary mirror according to our observations and consequently a greater power transfer between the two sites. A near infrared (808 nm) laser coupled into single mode fiber and suitably attenuated was used as source. The receiver at OGS uses a telescope with 1m primary mirror diameter equipped with single photon detector and suitable electronics.

We analyzed the overall losses of the free-space channel and temporal scintillation of the intensity at the receiver as a function of the atmospheric conditions. The intensity has been collected during many nights. From its analysis we infer that for this scale length the distribution follows the lognormal distribution [4], extending by more than a decade the observations of Ref. [5]. The scintillation index and the possible use of Adaptive Optics are discussed.

Session VI: Vision / 66

Functional Imaging of Single Cells in the Living Eye

Author: David Williams¹

¹ *Dean for Research in Arts, Science, and Engineering Director, Center for Visual Science William G. Allyn Professor of Medical Optics*

Abstract content
(Max 300 words)
Special Chars:

The correction of the eye's aberrations with adaptive optics has made it possible to image the normal and diseased retina of the living eye at microscopic resolution. I will describe recent developments in the deployment of this technology, many of which combine AO and other imaging modalities with the goal of obtaining not only structural but also functional information at a cellular or subcellular spatial scale. I will illustrate the value of this approach with examples including single photon fluorescence imaging of retinal pigment epithelial cells in macular degeneration, the use of genetically encoded calcium indicators to record the neural response of individual ganglion cells in the intact eye, the use of interferometry to measure the dimensions of photoreceptors, as well as methods to measure the flow of blood cells in single capillaries noninvasively. I will also describe recent advances in two-photon

imaging in the living eye, which allow us to optically probe molecular events in retinal cells that would otherwise be inaccessible.

67

Welcome Remarks

Corresponding Author: aforbes1@csir.co.za

Introductory lectures on the core technology / 68

Basics of AOs and adaptive control

Corresponding Author: kud@activeoptics.ru

Introductory lectures on the core technology / 69

Basics of deformable mirrors

Corresponding Author: wittrock@fh-muenster.de

Introductory lectures on the core technology / 70

Basics of wavefront sensing

Corresponding Author: sergio.restaino@nrl.navy.mil

71

Basics of liquid crystals and their use in AOs:

Corresponding Author: aforbes1@csir.co.za

Introductory lectures on applications in medicine and health / 72

AOs in Vision

Corresponding Author: pablo@um.es

Introductory lectures on applications in medicine and health / 73

Biomedical imaging with AOs

Corresponding Author: g.d.love@durham.ac.uk

Introductory lectures on applications in medicine and health / 74

AOs and microscopy

Corresponding Author: martin.booth@eng.ox.ac.uk

Introductory lectures on current state-of-the art AO systems / 75

Turn key AO systems

Corresponding Author: pab@bostonmicromachines.com

Introductory lectures on current state-of-the art AO systems / 76

AOs in ultrafast and ultrahigh power lasers

Corresponding Author: lancis@uji.es

Introductory lectures on current state-of-the art AO systems / 77

AOs in high precision materials

Corresponding Author: martin.booth@eng.ox.ac.uk

Session IV: Adaptive Control / 78

Wavefront correction in large-scale glass laser LFEX

Author: Takahisa JITSUNO¹

Co-authors: N Miyanaga¹; N Morio¹

¹ *Institute of Laser Engineering, Osaka University, JAPAN*

Abstract content
(Max 300 words)
Special Chars:

LFEX laser system is a large-scale glass laser with output energy of 12 kJ and pulse duration of 1~10 ps. In this laser system, 8 deformable mirrors (DFM) are used in 4 beam-lines. We are planning to introduce additional large scale (40 x 46 cm) Bimorph DFM for pulse compression and focusing. Details of our DFM development will be reported

Session VIII : Spatial Light Modulators / 79

Real-time dynamic control of laser modes**Author:** Sandile Ngcobo¹**Co-authors:** Andrew Forbes¹; Igor Litvin²; Liesl Burger³¹ CSIR² CSIR NLC³ National Laser Centre**Corresponding Authors:** lburger1@csir.co.za, ilitvin@csir.co.za, aforbes1@csir.co.za, sngcobo@csir.co.za**Abstract content** (Max 300 words) [Special Chars](http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=28):

Adaptive optics has been used in many optical systems to correct the amount of wavefront distortions for application such as laser ranging, free space optical communication and medical imaging of retinas. In these optical systems the correction of the wavefront is usually performed using deformable mirrors where a wavefront sensor is typically used to measure the distortions the atmosphere has introduced on the timescale of a few milliseconds. The optimal mirror shape for correcting the distortions is then calculated using a computer and the surface of the deformable mirror will then be reshaped accordingly. The reshaping of the mirror has been shown to have a limited stroke in the phase profiles that it can accommodate and thus have found little application in laser mode shaping. We have overcome this limitation with the first digital laser comprising an electrically addressed reflective phase-only spatial light modulator (SLM) as an intra-cavity holographic mirror where the amplitude and phase of the mirror are controlled by writing a new computer generated gray scale image on the SLM. We demonstrate that a digitally controlled digital laser for on-demand laser mode can be used to generate distortion-corrected laser modes by switching between several spatial modes in a standard solid state laser resonator.

Session X: Propagation and Turbulence / 80

Quantum communication with OAM entangled photons**Author:** Alpha Hamadou Ibrahim¹**Co-authors:** Andrew Forbes²; Filippus Roux³; Melanie McLaren²; Thomas Konrad⁴¹ CSIR, National Laser Center² CSIR³ CSIR National Laser Centre⁴ UKZN**Corresponding Authors:** fsroux@csir.co.za, konradt@ukzn.ac.za, aforbes1@csir.co.za, aibrahim@csir.co.za**Abstract content** (Max 300 words) [Special Chars](http://indico.saip.org.za/getFile.py/access?resId=0&materialId=2&confId=28):

We consider Laguerre-Gaussian modes to study the evolution of an OAM entangled bipartite photonic state in atmospheric turbulence. Photon pairs are generated via spontaneous parametric down-conversion and one photon from each pair is propagated through turbulence. To compare our results with previous work, the turbulent atmosphere is simulated with a single phase screen based on the Kolmogorov theory of turbulence and we only consider two level photonic quantum system (qubits). A full quantum state tomography is performed to reconstruct the two-qubit density matrices for a range of scintillation strengths and the concurrence is used as a measure of entanglement. Our results show how the initial OAM mode is increasingly scattered into neighbouring modes as we increase the scintillation strength. We compare the evolution of entanglement for different values of the OAM and we show how entanglement evolution in turbulence depends on the OAM value used.

81

Producing Kaleidoscope Modes using the Digital Laser

Author: L Burger¹

¹ CSIR - NLC

Corresponding Author: lburger1@csir.co.za

Abstract content
(Max 300 words)
Special Chars:

With ruggedness inherent in its optical design, the Porro prism laser has been widely used for many years in field applications, for example in the lasers used in range finding and target designation systems. A “petal” mode is commonly produced by these systems, but until recently the formation of these modes was not understood. Our previous work uses symmetry arguments to explain how these modes are formed, and a physical optics model based on these principles produces the observed petal modes. By increasing the transverse area available to the beam this model predicts novel modes, dubbed “kaleidoscope modes”, and later shown to be Laguerre modes. However, relying as they do on perfect symmetry and alignment, these modes are difficult to produce. We demonstrate that with our new “digital laser” we are able to produce these modes on demand, opening up the field of study of high-order Laguerre modes.