



Contribution ID: 21

Type: Oral Presentation

## Characterisation of $\text{Y}_{2}\text{O}_{3}$ co-doped $\text{Bi}^{3+}$ and $\text{Yb}^{3+}$ thin films synthesised using pulsed laser deposition and spin coating.

*Tuesday, 26 June 2018 11:20 (20 minutes)*

Phosphor materials doped with various rare-earth (RE) elements have been used by the lighting industry in light emitting diodes and mercury free fluorescent tubes due to the wide range of possible luminescence ranging from ultraviolet (UV) through to the near-infrared (NIR) regions. In recent years, phosphor materials have been used to alter the solar spectrum in order to reduce the spectral mismatch and improve the conversion efficiency of solar cells.  $\text{RE}^{3+}$  -  $\text{Yb}^{3+}$  co-doped phosphors have shown potential for down-converting/shifting UV photons to NIR photons, but due to the parity forbidden  $4f$  transition of  $\text{RE}^{3+}$ , they are generally inefficient at absorbing photons in the UV and blue regions resulting in a weak NIR  $\text{Yb}^{3+}$  emission. Metal donor ions such as  $\text{Bi}^{3+}$  have shown to be an alternative to rare-earth ions for enhancing the NIR emission of  $\text{Yb}^{3+}$  ions.  $\text{Y}_{2}\text{O}_{3}:\text{Bi}^{3+},\text{Yb}^{3+}$  thin films were prepared using the pulsed laser deposition (PLD) and spin coating techniques. For films prepared through spin coating we found that the molarity of the  $\text{Y}_{2}\text{O}_{3}:\text{Bi}^{3+},\text{Yb}^{3+}$  solution plays an important role in the smoothness of the prepared films. Scanning electron microscopy analysis showed that films prepared at concentrations greater than 0.4 M were rough and dispersed with large agglomerations in the order of 100  $\mu\text{m}$ , while films prepared at 0.2 M were significantly smoother and no agglomerations. Films synthesised using PLD also showed a rough surface, however the size of the agglomerated particles were approximately 1  $\mu\text{m}$ . These small agglomerations were expected due to the laser ablation process which has an explosive-like character. Finally, under UV (325 nm) excitation the photoluminescence analysis for both the PLD and spin coating synthesised thin films yielded good luminescence properties in both the visible and more importantly in the NIR region. The result demonstrated that UV to NIR down-conversion/shifting is possible and may be used to modify the solar spectrum with the aim of improving the efficiency of solar cells.

**Please confirm that you have carefully read the abstract submission instructions under the menu item "Call for Abstracts" (Yes / No)**

Yes

**Consideration for student awards** Choose one option from those below.

N/A  
Hons  
MSc  
PhD

**Supervisor details** If not a student, type N/A. Student abstract

**submission<br>requires supervisor permission:<br>please give their name,<br>institution and email address.**

Prof HC Swart  
University of the Free State  
SwartHC@ufs.ac.za

**Primary authors:** Mr LEE, Edward (University of the Free State); Prof. SWART, Hendrik (University of the Free State)

**Co-authors:** Prof. TERBLANS, JJ (Koos) (UFS); Prof. KROON, R. E. (University of the Free State); Dr CRACIUN, Valentin (National Institute for Lasers, Plasma and Radiation Physics, Magurele, Romania)

**Presenter:** Mr LEE, Edward (University of the Free State)

**Session Classification:** Physics of Condensed Matter and Materials

**Track Classification:** Track A - Physics of Condensed Matter and Materials