



Contribution ID: 294

Type: Oral Presentation

## Comparative Efficiency Study of a Solar Trough Receiver: Hot mirror and Selective coating

Wednesday, 13 July 2011 12:15 (15 minutes)

We consider a solar trough system in which cylindrical parabolic mirrors focus the sun's radiation onto a receiver pipe, heating it. Conventionally, the pipe is enclosed in a glass cover under vacuum and the dominant radiation losses are reduced by the use of a selective coating on the receiver pipe. We study the suitability of applying a 'hot mirror' coating on the glass cover instead, which transmits in the visible but reflects well in the infra-red. We compare the performance of the 'selective' with a 'hot mirror' coating using the results from simulations for a general heat transfer model. It is seen that a hot mirror is a viable alternative, and certainly allows higher temperatures of the working fluid and therefore higher Carnot efficiency. The optimum is a hybrid system, with selective coating applied at the low temperature end of the receiver pipe and the hot mirror being used at higher temperatures.

**Level (Hons, MSc, &nbsp; PhD, other)?**

I am a Msc student

**Consider for a student &nbsp; award (Yes / No)?**

yes

**Would you like to <br> submit a short paper <br> for the Conference <br> Proceedings (Yes / No)?**

Yes

**Primary author:** Ms CYULINYANA, Marie Chantal (University of the Witwatersrand)

**Co-author:** Dr FERRER, Philippe (University of the witwatersrand)

**Presenter:** Ms CYULINYANA, Marie Chantal (University of the Witwatersrand)

**Session Classification:** Applied

**Track Classification:** Track F - Applied and Industrial Physics