



Contribution ID: 122

Type: Oral Presentation

Reversible Semiconductor – Metal Transition study in nano-FePt system

Wednesday, 13 July 2011 14:15 (15 minutes)

Highly crystalline nano-spherical Fe-Pt systems were produced by 248 nm laser irradiation of liquid precursor at different laser fluence ranging from 100 – 375 mJ/cm². The influence of laser intensity on the particle size, iron composition and vibrational properties was systematically investigated. The study reveals that the larger particles have higher iron content. The prepared precursor solution through Fe (III) acetylacetonate and Pt (II) acetylacetonate underwent a deep photolysis to polycrystalline of nano Fe-Pt alloys. Fe (II) and Pt (I) acetylacetonate decompose into Fe₀ and Pt₀ nanoparticles (NPs). The material is shown to contain only iron and platinum by EDS. We have observed hysteretic loop in structural phase transition of Fe₆₀Pt₄₀ NPs. The material shows high resistance (2,700 Ohms) at lower temperatures and low resistance (2,200 Ohms) at higher temperatures. Pan theory was used to exemplify the phase transition.

**Level (Hons, MSc,
 PhD, other)?**

PhD

**Consider for a student
 award (Yes / No)?**

Yes

**Would you like to
 submit a short paper
 for the Conference
 Proceedings (Yes / No)?**

Yes

Primary author: Mr NKOSI, Steven (CSIR and University of the Witwatersrand)

Co-author: Prof. SIDERAS-HADDAD, Elias (University of the Witwatersrand)

Presenter: Mr NKOSI, Steven (CSIR and University of the Witwatersrand)

Session Classification: CMPMS1

Track Classification: Track A - Condensed Matter Physics and Material Science